

**Microfluidic System Including a Virtual Wall Fluid Interface Port for Interfacing
Fluids with the Microfluidic System**

5 Reference to Related Applications

This application claims priority to U.S. Provisional Patent Application No. 60/299,515 filed June 20, 2001, and is related to Attorney Docket No. CVZ-001a, entitled "Microfluidic System Including a Virtual Wall Fluid Interface Port for Interfacing Fluids with the Microfluidic System", filed herewith; Attorney Docket No.

10 CVZ-001b, entitled "Microfluidic System Including a Virtual Wall Fluid Interface Port for Interfacing Fluids with the Microfluidic System", filed herewith; Attorney Docket No. CVZ-002, entitled "Microfabricated Two-Pin Liquid Sample Dispensing System", filed herewith; Attorney Docket No. CVZ-003, entitled "Small Molecule Substrate Based Enzyme Activity Assays", filed herewith; and Attorney Docket No. CVZ-005,
15 entitled "Droplet Dispensing System", filed herewith. The contents of the foregoing patent applications are herein incorporated by reference. The contents of all references, issued patents, or published patent applications cited herein are expressly incorporated by reference.

20 Field of the Invention

The present invention relates to microscale fluid handling devices and systems. More particularly, the present invention relates to fluidic interface ports for providing bi-directional fluid interfacing in a microfluidic system.

25 In the chemical, biomedical, bioscience and pharmaceutical industries, it has become increasingly desirable to perform large numbers of chemical operations, such as reactions, separations and subsequent detection steps, in a highly parallel fashion. The high throughput synthesis, screening and analysis of (bio)chemical compounds, enables the economic discovery of new drugs and drug candidates, and the implementation of
30 sophisticated medical diagnostic equipment. Of key importance for the improvement of the chemical operations required in these applications are an increased speed, enhanced reproducibility, decreased consumption of expensive samples and reagents, and the reduction of waste materials.

Microfluidic devices and systems provide improved methods of performing chemical, biochemical and biological analysis and synthesis. Microfluidic devices and systems allow for the performance of multi-step, multi-species chemical operations in chip-based micro chemical analysis systems. Chip-based microfluidic systems generally comprise conventional 'microfluidic' elements, particularly capable of handling and analyzing chemical and biological specimens. Typically, the term microfluidic in the art refers to systems or devices having a network of processing nodes, chambers and reservoirs connected by channels, in which the channels have typical cross-sectional dimensions in the range between about 1.0 μm and about 500 μm . In the art, channels having these cross-sectional dimensions are referred to as 'microchannels'.

By performing the chemical operations in a microfluidic system, potentially a number of the above-mentioned desirable improvements can be realized. Downscaling dimensions allows for diffusional processes, such as heating, cooling and passive transport of species (diffusional mass-transport), to proceed faster. One example is the thermal processing of liquids, which is typically a required step in chemical synthesis and analysis. In comparison with the heating and cooling of liquids in beakers as performed in a conventional laboratory setting, the thermal processing of liquids is accelerated in a microchannel due to reduced diffusional distances. Another example of the efficiency of microfluidic systems is the mixing of dissolved species in a liquid, a process that is also diffusion limited. Downscaling the typical dimensions of the mixing chamber thereby reduces the typical distance to be overcome by diffusional mass-transport, and consequently results in a reduction of mixing times. Like thermal processing, the mixing of dissolved chemical species, such as reagents, with a sample or precursors for a synthesis step, is an operation that is required in virtually all chemical synthesis and analysis processes. Therefore, the ability to reduce the time involved in mixing provides significant advantages to most chemical synthesis and analysis processes.

Furthermore, reduced dimensions enhance separation operations utilized in chemical synthesis and analysis processes. One example is capillary electrophoresis, which is a separation technology based on the migration of dissolved charged species

through a liquid filled capillary by the application of a longitudinal electric field. By reducing the cross-sectional size of the capillaries, the separation efficiency can greatly be improved, thereby resulting in rapid separations. For examples, see Effenhauser et al., Anal. Chem. 65:2637-2642 Oct. (1993), Effenhauser et al., Anal. Chem. 66:2949-2953 Sep. (1994), Jacobson et al., Anal. Chem. 66:4127-4132 Dec. (1994) and Jacobson et al., Anal. Chem. 66:1114-1118 Apr. (1994).

Another aspect of the reduction of dimensions is the reduction of required volumes of sample, reagents, precursors and other often very expensive chemical substances. Milliliter-sized systems typically require milliliter volumes of these substances, while microliter sized microfluidic systems only require microliters volumes. The ability to perform these processes using smaller volumes results in significant cost savings, allowing the economic operation of chemical synthesis and analysis operations. As a consequence of the reduced volume requirement, the amount of chemical waste produced during the chemical operations is correspondingly reduced.

It can be concluded that due to the reduced dimensions associated with microfluidic systems, important chemical operations can be accelerated whilst at the same instance lead to a reduction of consumption of chemicals and chemical waste.

Applications of microfluidic systems are myriad. For example U.S. Pat. No. 5,922,591 describes a miniaturized integrated nucleic acid diagnostic device and system. This device is capable of performing one or more sample acquisition and preparation operations, in combination with one or more sample analysis operations. Useful applications for microfluidic systems are in nucleic acid based diagnostics and de novo sequencing applications. International Patent Appln. WO 96/04547, published Feb. 15, 1996, describes the use of electro-kinetic operated microfluidic systems for performing electrophoretic separations, flow injection analysis and chemical reactions and synthesis steps. U.S. Pat. No. 5,942,443 discloses a range of microfluidic devices and methods for performing high-throughput synthesis and analysis, especially useful in screening a large number of different chemical compounds for their effect on a variety of chemical and biochemical systems. U.S. Pat. No. 5,858,804 provides a method of performing an immunological assay in a micro-laboratory array comprising a plurality of

microchannels and chambers disposed in a solid substrate. U.S. Pat. No. 6,176,991 B1 discloses a serpentine electrophoresis channel in microchip format providing efficient, high-speed analysis of the composition of chemical samples, especially for nucleic acid sequencing.

5

Many methods have been described for the interfacing of fluids, e.g., samples, analytes, reagents, precursors for synthesis and buffers, towards, within or between microfluidic systems. In conventional microfluidic systems, the structures and methods used to introduce samples and other fluids into microfluidic substrates limit the capabilities of the microfluidic systems. For example, conventional microfluidic systems may include a separate sample introduction channels for introducing a sample to a microchannel for processing. The sample is first introduced into the sample channel and transported through the sample channel to the microchannel. Another method for introducing a fluid involves the use of sample wells or reservoirs in communication with the microchannel for holding a relatively larger supply of the sample. Reservoirs are structures which accommodate a significantly greater volume of fluid than the microfluidic channel. A relatively small portion of the sample supply in the sample well or reservoir is introduced into the microchannel.

The total number of samples and other fluids that can be processed on a microfluidic substrate is currently limited by the size and/or the number of reservoirs through which these fluids are introduced to the microfluidic system. A disadvantage of known structures and methods for introducing fluids into a microfluidic system is the use and transfer of a much greater volume of fluid than is needed for microfluidic analysis due to significant size inefficiencies and sample loss. Furthermore, with conventional methods of introducing fluids into microfluidic systems, it is difficult to control the amount of sample introduces that is eventually introduces into the microchannel after passing through a sample channel or a reservoir.

One method of fluidic communication with microfluidic systems is by mechanical micropumps and valves, see U.S. Pat. No. 6,033,191 and U.S. Pat. No. 5,529,465. A major disadvantage of this approach for fluidic interfacing is the complex construction and operation of these micropumps and valves. Another disadvantage is

there relatively large size and internal volume when compared to the internal volume of the microchannels. Often there are multiple orders of magnitude between these two volumes and the resulting discrepancy renders micropumps unattractive to interface with a large number of small dimensional microchannels.

5

U.S. Pat. No. 5,173,163 describes a method and device for introducing a fluidic sample in a micro-capillary for electrophoretic separation. In this method liquid is brought into a separation capillary by introducing one end of this capillary into a vessel containing the liquid to be introduced. A combination of applied external pressures and
10 voltages results in the transport of liquid from the vessel into the capillary. The proposed method has disadvantages. The size of the device does not allow the interfacing with a large number of microchannels, and between consecutive injections, the device needs to be cleaned, thereby considerably reducing throughput.

15 Another method for introducing materials in a microfluidic device is disclosed in U.S. Pat. No. 6,042,709. In this approach electrokinetic forces are employed to move a charged compound through a receiving inlet opening of the microfluidic device. A disadvantage is that the precise amount of injected liquids and substances depends upon a large number of factors which are difficult to control. One important parameter is the
20 surface potential of the microchannel wall, which together with the applied voltage determines the liquid flow. This surface potential depends on pH of the liquid to be pumped as well as its ionic composition and even the type of ions present in the liquid. It is also a disadvantage that it does not allow the efficient interfacing with a large number of different liquids as for every injection port, a separate high voltage supply is
25 required, together with the associated liquid channels for providing a closed electrical circuit.

A method and apparatus for performing electrophoretic experiments in a highly parallel fashion is disclosed in U.S. Pat. No. 6,103,199. Here, a plurality of separation
30 capillaries with associated wells for receiving chemical substances in fluid form are disposed in the form of a two dimensional array. The chemical substances are dispensed from a micro titer plate into these wells by an interfacing methodology employing pressurized chambers associated with the wells to be filled. A disadvantage is that only a

very small fraction of the applied liquid is actually introduced in the target microchannel, the bulk of the applied liquid drop remains behind in the well by capillary forces. As a result, most of the liquid is wasted and is not available for a consecutive chemical processing step. The effect that only a small portion of the liquid transported
5 actually is introduced in a targeted part of a microfluidic system, can be referred to as 'injection efficiency', i.e. the ratio between the volume of liquid required for a particular chemical operation in a part of the microfluidic system, and the total volume of liquid required for the introductory operation.

10 In this particular disclosure, only sub-nanoliter amounts are required for the electrophoretic separation (i.e. the chemical operation), whilst many microliters of sample are drawn from the micro titer plate (i.e. introductory operation), yielding an injection efficiency much less than 0.001. A low injection efficiency is disadvantageous because it indicates inefficient use of chemical substances and an increased production
15 of waste.

U.S. Pat. No. 6,090,251 provides micro-fabricated structures for facilitating fluid introduction into microfluidic devices. Fluid is introduced into a plurality of receiving wells in direct communication with associated microchannels, by the dropping of liquids
20 into these receiving wells using pressurized gas. Besides the complexity of the required fluidic manifolds and pressurizing system, also here a disadvantage is the inherently low injection efficiency as only a very small fraction of the applied liquid is actually used in the experiment.

25 For the introduction of liquids in capillary electrophoresis columns implemented on chip-like devices, generally electrokinetic injection is applied. See Woolley et al., Anal. Chem. 70:684-688 Feb. (1998), Jacobson et al., Anal. Chem. 68:720-723 Mar. (1996), Jacobson et al., Anal. Chem. 66:2369-2373 Jul. (1994) and Effenhauser et al., Anal. Chem. 67:2284-2287 Jul. (1995). In this method, liquid is pumped from a first
30 well towards the microchannel for electrophoretic separation by the application of a high driving voltage between this well and a second well located downstream. Due to the charged inner surfaces of the microchannel walls, an electroosmotic liquid flow is induced pumping liquid out of the first into the targeted microchannel. This method is

referred to as 'electrokinetic injection' and has some specific disadvantages. One disadvantage is that if a large number of liquids need to be handled, for instance in high-throughput synthesis and screening applications, a large number of wells need to be integrated on the microfluidic device. The relatively large footprint of a typical well (about 5 mm diameter) when compared to the microchannels in which the actual chemical operation is performed (about 50 μm diameter), takes up a dominating portion of the chip surface (see U.S. Pat. No. 6,143,152 and U.S. Pat. No. 6,159,353). As the costs of microfluidic chips strongly depends on the chip surface, the required integration of wells renders this liquid injection scheme unattractive for high-throughput synthesis and screening applications.

Another disadvantage of conventional systems is that for every well, a separate electrode is required together with electronic circuitry for the application of the driving voltages. This requirement results in a complex and expensive apparatus.

Another specific disadvantage with electrokinetic injection is the fact that during the application of the driving voltage on the electrode the electrolysis of water results in the generation of hydroxyl ions (OH^-), hydrogen ions (H^+), hydrogen gas (H_2) and oxygen gas (O_2). The generated ions will affect the acidity (i.e. pH) of the liquid pumped from the first well, whilst the produced gasses potentially give rise to the formation of gas bubbles in the microfluidic system thereby destroying the experiment and eventually the microfluidic device. Besides electrolysis of the aqueous medium, any present electroactive species can degrade due to electrochemical reactions at the electrode surface. For instance, the presence of chloride ions, an ion present in most liquid media, will result in the formation of chlorine gas, which on turn can interact and potentially destroy vulnerable (biochemical) compounds present in the liquid to be injected. Also the liquid to be injected can contain electroactive constituents which can be degraded by the electrochemical processes associated with electrokinetic injection. These disadvantages can be grouped and referred to as 'electrochemical pollution'.

Another disadvantage of electrokinetic injection is that in between consecutive experiments, the well need to be thoroughly cleaned in order to prevent cross-contamination. This required cleaning step results in a reduction of throughput and

makes it difficult to implement on-line monitoring. Another disadvantage is that the liquid to be injected is subjected to a high voltage. This aspect of the absence of galvanic separation makes it virtually impossible to use electrokinetic injection for in-vivo or near-vivo applications due to the danger of electrocution. Another disadvantage is that the electrokinetic injection methods referred to, are only applicable in chip like systems produced via microfabrication technology, i.e. via the use of expensive equipment and processes also applied for the fabrication of computer chips. These methods are known to have high costs. It is desirable to provide a n interfacing methodology which is also applicable in current non chip-based capillary systems. Still another disadvantage is the low injection efficiency of electrokinetic injection. To fill a typical well, about 10-50 μ l of liquid is required, whilst for a particular chemical operation only sub nanoliter amounts are required.

U.S. Pat. No. 6,130,098 discloses the movement of liquid volumes into and through microchannels by employing pressures generated by heating a volume of air in direct connection with these microchannels. A disadvantage of this fluidic interfacing method is that for a correct and efficient operation the pressure generating air chamber together with electronic heater components need to be integrated with the microfluidic system. This results in a complex device with associated large costs.

It can be concluded based on the above that current methods and systems for fluidic interfacing with microfluidic devices have particular disadvantages regarding the difficulty of integration of a large number of chemical operation nodes to interface with (i.e. electrochromatography columns, reactors etc.), relatively large required liquid volumes, low injection efficiency, electrochemical sample pollution, long rinse time between analysis steps, galvanic separation and required microfabrication technologies. Besides these disadvantages, none of the above mentioned interfacing methods allow bi-directional fluidic interfacing, i.e. transporting liquids to and from microfluidic systems. There has arisen a need in the art for providing suitable bi-directional fluidic interfacing structure that allows for the implementation of a much wider range of chemical operation steps in microfluidic systems.

Summary of the Invention

The present invention provides methods, devices and systems for interfacing fluids in microfluidic systems. A fluid interface port for directly interfacing a microfluidic channel network and the surrounding environment is provided in a microchannel in a microfluidic system by forming an opening in a side wall of the microchannel. The aperture forms a virtual wall when the microchannel is filled with a liquid. The aperture has suitable cross sectional dimensions such that capillary forces retain liquid within the microchannel. The virtual wall is defined by the meniscus of the liquid in the opening, which essentially replaces the side wall of the microchannel so as to not substantially affect or influence fluid flow through the microchannel.

Filling of a microchannel may be accomplished via the opening in the side wall of the microchannel. To fill the microchannel, a user forms droplets of a first liquid and directs the droplet towards the opening, such that the droplets of the first liquid enter and fill the microchannel.

Fluid introduction and/or fluid removal is accomplished through a virtual wall formed in the side wall of a microchannel. The process of introducing a fluid sample to the microchannel comprises forming a droplet of the fluid and propelling the droplet towards a virtual wall. The droplet traverses the virtual wall and enters the microchannel directly, without requiring intermediate reservoirs or channels. The virtual wall formed in the side wall of the microchannel may also define a fluid ejection port for ejecting a fluid from the microchannel in the form of a droplet.

According to a first aspect of the invention, a method of forming a fluid interface port in a microfluidic system is provided. The method comprises forming at least a portion of a microchannel in a substrate, and forming a fluid interface port along a length of the channel having suitable dimensions to form a virtual wall therein when the microchannel is filled with a liquid.

According to another aspect, a microfluidic structure is provided, comprising a substrate, one or more microchannels formed in the substrate, a cover for covering the microchannel, wherein said microchannel includes a side wall, and one or more fluid

interface ports formed in the cover along the length of the microchannel, wherein a virtual wall is formed in the fluid interface port when a fluid is disposed in the microchannel.

- 5 According to another aspect of the invention, a method of rendering an interior surface of a microchannel hydrophobic is provided. The method comprises providing a microchannel having an interior bounded by a side wall and a fluid interface port comprising an aperture formed in the side wall to provide access to the interior of the microchannel and introducing a hydrophobic material to the interior through the
- 10 aperture. The hydrophobic material forms a hydrophobic patch on an interior surface of the side wall that is coaxially aligned with the aperture.

- According to yet another aspect of the invention, a method of manufacturing a microfluidic chip is provided. The method of manufacture comprises providing a first
- 15 planar sheet having a recess formed in a top surface therein, applying a middle layer to the first planar sheet and removing a portion of the middle layer to define a channel and a fluid interface port in communication with the recess. The fluid interface port is sized and dimensioned such that when a fluid is disposed in the recess and channel, the fluid forms a virtual wall at the fluid interface port. The method further comprises the steps
- 20 of applying a second planar sheet to the first planar sheet, and removing a portion of the second planar sheet to define an access hole in communication with the fluid interface port.

Brief Description of the Drawings

- 25 Figure 1 is a schematic view of a microfluidic system suitable for implementing the illustrative embodiment of the invention.

 Figure 2a is a top view of a microchannel structure having a fluid interface port formed in a side wall of the microchannel for filling the microchannel with a first fluid according to the teachings of the invention.

- 30 Figure 2b is a cross-sectional view of the microchannel of Figure 2a along the length of the microchannel.

 Figures 3a and 3b illustrate the steps of filling the microchannel of Figure 2a with a first fluid by directing droplets of the first fluid through the fluid interface port.

Figure 4a illustrates the microchannel of Figures 2a and 2b further including a hydrophobic patch disposed in the microchannel interior according to an alternate embodiment of the present invention.

Figure 4b illustrates an alternate embodiment of a microchannel according to the teachings of the invention, wherein the hydrophobic patch is coaxially arranged with a fluid interface port.

Figure 5a is a top view of a microchannel according to one embodiment, including a filling aperture and a stopper hole for directing the filling of a first fluid in the microchannel according to the teachings of the invention.

Figure 5b is a cross-sectional view of the length of the microchannel shown in Figure 5a, illustrating the process of filling the microchannel.

Figure 6 illustrates the filling of a microchannel with two different fluids by utilizing a plurality of filling apertures disposed in the side wall of the microchannel.

Figure 7a illustrates the process of closing the filling aperture of Figures 2a through 6 by forming and dispensing drops of encapsulant onto the filling aperture according to one embodiment of the present invention.

Figure 7b illustrates the process of closing the filling aperture using a covering layer according to an alternate embodiment of the present invention.

Figure 8 illustrates a microchannel having a filling aperture located adjacent to a closed end of the microchannel, such that the introduction of droplets into the microchannel through the filling aperture induces a flow in the microchannel.

Figure 9a is a cross-sectional side view of a microchannel including a fluid interface port for receiving a liquid droplet into the microchannel.

Figure 9b is a cross-sectional view perpendicular through the microchannel of Figure 9a at the position of the fluid interface port, illustrating the insertion of a drop using a pin.

Figure 9c is a cross-sectional view of a microchannel having a virtual wall according to the teachings of the invention, illustrating the composition of the liquid inside the microchannel directly after receiving a droplet.

Figure 9d illustrates a microchannel having a virtual wall according to the teachings of the invention, immediately after injection of the second liquid in the first liquid, whereby the first and second liquid are immiscible.

Figure 9e is a cross-sectional view of a microchannel having a virtual wall according to an alternate embodiment of the invention.

Figure 9f is a cross-sectional view of a microchannel having a virtual wall according to an alternate embodiment of the invention, including a covering layer.

5 Figure 9g is a cross-sectional view of a microchannel having an array of apertures forming virtual walls.

Figure 9h illustrates the introduction of a liquid into the microchannel shown in Figure 9g.

10 Figure 10a illustrates a microchannel having a plurality of virtual walls disposed across the radial width of the microchannel according to one embodiment of the present invention.

Figure 10b illustrates a microchannel having a plurality of virtual walls disposed along the axial length of the microchannel according to one embodiment of the present invention.

15 Figure 11a is a schematic block diagram representative of a sample introduction system for electrically guiding a selected droplet into a selected microchannel according to the teachings of the present invention.

20 Figure 11b is a cross-sectional view of a microchannel array of Figure 4a of the present invention wherein microchannels can selectively be charged to attract or repel a selected droplet according to the teachings of the present invention.

Figure 11c is a cross-sectional view of the microchannel array of Figure 11a employing an array of ring electrodes for guiding a selected droplet into a selected microchannel according to the teachings of the present invention.

25 Figure 12a is a schematic view of one embodiment of the present invention for ejecting liquid from a microchannel through a virtual wall by using electric fields.

Figure 12b is a schematic view of an alternate embodiment of the present invention for ejecting liquid from a microchannel through a virtual wall by the application of pressure pulses to the liquid.

30 Figure 12c is a schematic view of still another embodiment of the present invention for ejecting liquid from a microchannel through a virtual wall by the application of a gas pressure pulse to the liquid.

Figure 12d is a schematic view of yet another embodiment of the present invention for ejecting liquid from a microchannel through a virtual wall by a gas bubble.

Figure 13a is a cross-sectional view of a microchannel with a single virtual wall wherein liquid inside the microchannel is optically verified via the virtual wall.

Figure 13b is a cross-sectional view of a microchannel in which two concentric virtual walls are diametrically opposed, and demonstrates optical detection using both
5 virtual walls.

Figure 14 is a top view of an embodiment of the invention, illustrating the use of a microchannel having a virtual wall to perform a separation.

Figure 15 shows a cutaway view of an embodiment of the invention in which a plurality of virtual walls are employed for performing multi-step chemical experiments.

10 Figure 16 is a schematic cross-sectional view of an embodiment of the present invention in which a microchannel having a virtual wall part of an electrokinetically operated microfluidic system.

Figure 17 shows a perspective view of an embodiment according to the invention in which a plurality of microchannels with virtual walls is applied in an
15 electrokinetically operated microfluidic system.

Figure 18 illustrates an application of the virtual wall interface ports of an illustrative embodiment to interface a microfluidic system with a mass spectrometer.

Figure 19a is an exploded view of a microfluidic chip manufactured according to the teachings of the invention.

20 Figure 19b is a top view of the microfluidic chip of Figure 19a.

Figure 19c is a side view of the microfluidic chip of Figure 19a.

Figures 20a-c illustrate the steps of manufacturing a microchannel having an opening suitable for forming a virtual wall according to an embodiment of the present invention.

25 Figures 21a-21c illustrate the steps of manufacturing a microchannel with a virtual wall interface port according to another embodiment of the present invention.

Figures 22a-22c illustrate the steps of manufacturing a microchannel having a virtual wall as a fluidic interface port according to an alternate embodiment of the present invention.

30 Figure 23a is a perspective view and of a microchannel with a virtual wall in which a hydrophobic patch is disposed in the microchannel.

Figure 23b shows the use of the microchannel with the virtual wall depicted in Figure 23a.

Detailed Description of the Invention

The present invention provides an improved fluidic interface for introducing fluids to and removing fluids from a microchannel in a microfluidic system. The invention further provides a method of forming the fluidic interface. The present invention significantly improves controllability over fluid samples, increases injection efficiency and reduces waste by utilizing an opening defining a virtual wall in a side wall of a microchannel to introduce and remove fluids.

One or more of the illustrative embodiments allow bi-directional fluidic interfacing to and from microfluidic systems. With the present invention, a large number of chemical operations can be performed on a small chip surface, thereby enabling the cost effective implementation and efficient operation of massively parallel synthesis and analysis systems. The present invention further significantly reduces the required liquid volume for interfacing, resulting in a considerable reduction of consumption of chemicals as well as the reduction of chemical waste. The present invention further provides methods and systems for the injection of liquids with near 100% injection efficiency and provides methods and systems for the injection of liquids which do not electrochemically pollute the handled liquids. The present invention presents methods and systems for the fast repetitive injection of liquids in microfluidic systems, pressure driven as well as electrokinetically driven, allowing high throughput synthesis, screening and analysis applications. The present invention further allows for galvanic separation of the liquid to be injected with the electrokinetically operated microfluidic system. The invention further provides fluidic interfacing with microfluidic systems devices and system that are not necessarily manufactured using standard microfabrication technologies. For example, the invention provides for interfacing with standard fused silica capillaries. The present invention applies to a variety of liquid samples, including solutions of compounds, whole cells or cell lysates, enzymes, proteins or peptides, and particles.

Figure 1 illustrates a microfluidic system suitable for implementing the illustrative embodiment of the present invention. The illustrative microfluidic system 10 comprises a substrate 11 having one or more microchannels 3 disposed therein. The microchannels transport fluid through the microfluidic system 10 for processing,

handling, and/or performing any suitable operation on a liquid sample. As used herein, the term “microfluidic” refers to a system or device for handling, processing, ejecting and/or analyzing a fluid sample including at least one channel having microscale dimensions. The term “channel” as used herein refers to a pathway formed in or
 5 through a medium that allows for movement of fluids, such as liquids and gases. The term “microchannel” refers to a channel preferably formed in a microfluidic system or device having cross-sectional dimensions in the range between about 1.0 μm and about 250 μm , preferably between about 25 μm and about 150 μm and most preferably between about 50 μm and about 100 μm . One of ordinary skill in the art will be able to
 10 determine an appropriate volume and length of the microchannel. The ranges are intended to include the above-recited values as upper or lower limits. The microchannel can have any selected shape or arrangement, examples of which include a linear or non-linear configuration and a U-shaped configuration. The microfluidic system 10 may comprise any suitable number of microchannels 3 for transporting fluids through the
 15 microfluidic system 10.

According to one practice, the microchannel of the present invention can include a fluid interface port. As used herein, “fluid interface port” refers to a structure in a microfluidic system, such as an aperture formed in a microchannel, which provides fluid
 20 access between the interior and the exterior of a microchannel. The fluid interface port is utilized to introduce fluids and other material to the microchannel and/or to remove fluid and/or other material from the microchannel. The fluid interface port may comprise, among other applications, a filling port for filling the microchannel with a carrier liquid, a sample introduction port for introducing a sample into the microchannel
 25 and an ejection port for ejecting fluid from the microchannel.

According to the illustrative embodiment, the microchannel is defined by a side wall having any suitable shape enclosing at least a portion of the interior of the channel. The fluid interface port is formed in the side wall of the microchannel by removing a
 30 portion of the side wall to define an opening. The fluid interface port of the illustrative embodiment is formed by an aperture in the side wall of the microchannel having a diameter of between about 0.1 μm and about 200 μm and preferably between about 25 μm and about 125 μm and most preferably between about 50 μm and about 100 μm .

The aperture forming the fluid interface port may have any suitable shape, including, but not limited to, a cylinder, a disk, a conical shape, an elliptical shape and a cubic shape. The side wall or wall of the microchannel can be formed by two or more components that bound the entire volume of the microchannel. According to a first aspect of the invention, the fluid interface port is utilized to fill the microchannel with a first liquid. The first liquid comprises a carrier fluid for transporting a sample, reagent or other suitable liquid for performing one or more chemical operations, such as reactions and separations. Fluid flow may be induced in the microchannel via any suitable means, including, but not limited to, pressurizing and electroosmotic means.

As illustrated in Figures 2a through Figure 7, the fluid interface port 17 formed in the side wall of the microchannel forms a filling aperture or microaperture for filling the microchannel with the first liquid. Typically, conventional microchannels are filled by inserting the end of the microchannel into a reservoir containing the first liquid. Capillary forces pull the first liquid into the microchannel and thereby fill the microchannel with the first liquid. In order to avoid this procedure, the present invention employs a fluid interface port formed in the side wall (not end) of the microchannel. This enables a user to fill the microchannel through the port to provide simple, fast and efficient filling without requiring a large, separate liquid reservoir.

Figure 2a is a top view of a microchannel structure 3 comprising a side wall 16 surrounding a hollow interior. The microchannel includes a fluid interface port 17 located in the side wall 16 of the microchannel structure. The fluid interface port 17 may have any suitable shape based upon the intended use, examples of which include circular, cylindrical, elliptical and conical. Figure 2b is a cross-sectional view of the microchannel structure taken along the length of the microchannel 3, showing the fluid interface port 17 disposed in the top side of the microchannel. As shown, the interior of the microchannel 3 is initially empty. According to the illustrative embodiment, the microchannel 3 is filled with a first liquid via the fluid interface port 17 formed in the side wall 16 of the microchannel.

Figures 3a and 3b illustrate the process of filling the microchannel structure 3 with a first liquid 4 by directing droplets 4a of the first liquid 4 toward the fluid interface

port 17. The droplets 4a enter the microchannel 3 through the fluid interface port 17 and form a plug 13 of the first liquid 4 within the microchannel 3. As more droplets 4a are introduced via the fluid interface port 17, the plug 13 expands in both directions through the microchannel, as indicated by the arrows, thereby filling the microchannel along the length of the microchannel with the first liquid 4. Moreover, capillary forces work to draw the liquid 4 along the length of the microchannel 3. According to the illustrative embodiment, the first liquid 4 forms a meniscus in the fluid interface port 17 when the microchannel is filled and the liquid is retained in the microchannel by capillary forces.

The fluid interface port 17 is sized and dimensioned to form a virtual wall 15 when the microchannel is filled with the first liquid 4. As used herein, “virtual wall” refers to the meniscus formed by the first liquid 4 in the port 17 formed in the side wall of the microchannel. The meniscus surface can be, although not required, substantially co-planar with the wall 16 of the microchannel in which the meniscus is formed. The meniscus essentially replaces the removed portion of the side wall that defines the aperture 17. The word “virtual” is chosen to express the effect that the overall liquid flow through the microchannel of the microfluidic system is not influenced by the virtual wall, i.e. the flow of liquid in the microfluidic system having a virtual wall is substantially identical to the flow of liquid through an identical microfluidic system in which no virtual wall is present. The fluid interface port, according to one practice, has appropriate dimensions and surface properties as to substantially not influence the overall liquid flow and liquid shape when compared to a microfluidic system in which no port or meniscus is formed. The virtual wall forms a direct interface between the microchannel interior 5 and the microchannel exterior, allowing direct access to the liquid in microchannel 3 without introducing dead or unswept volume in the microchannel 3. The virtual wall also serves to seal liquid inside of the microchannel through a range of pressures in the microchannel. Those of ordinary skill will readily recognize that the surface or wall of the fluid interface port can be formed anywhere along the axial height of the port. One of ordinary skill will recognize that the meniscus may be convex or concave, depending on the appropriate system pressure.

According to an alternate embodiment, shown in Figure 4a, a hydrophobic patch 23 is applied to the side wall or interior of the microchannel 3 prior to introduction of

the first liquid 4. When the first liquid 4 is introduced to the microchannel, the hydrophobic patch 23 forms a barrier, and causes the plug 13 of liquid 4 to expand only in one direction, away from the patch 23.

5 According to one embodiment, shown in Figure 4b, the hydrophobic patch 23 is applied to the interior surface of the microchannel through an aperture forming a fluid interface port 17 in the side wall 16 of the microchannel. The hydrophobic patch 23 may comprise any suitable material for rendering a surface hydrophobic, such as gold. The hydrophobic material may be sputtered, evaporated, sprayed or deposited through
10 the aperture 17 and bound to the interior surface of the microchannel 3 opposite the aperture to form the hydrophobic patch 23. One skilled in the art will recognize that any suitable surface treatment for the microchannel may be applied through the aperture, in addition to hydrophobic patches.

15 The aperture used to apply the hydrophobic patch 23 may further serve as a vent for the microchannel 3 to allow air to escape from the microchannel interior. As shown, the aperture is coaxially arranged with the hydrophobic patch. The actual vent, formed by the aperture 17 in the side wall, is not hydrophobic. However, the microchannel surface coaxially opposite the vent is rendered hydrophobic by application of the
20 hydrophobic patch 23. The hydrophobic region is not flushed by liquid, allowing air to escape the microchannel interior through the aperture 17 in the side wall 16.

 According to yet another embodiment, shown in Figures 5a and 5b, the microchannel 3 further includes a stopper hole 28 adjacent to the fluid interface port 17.
25 The stopper hole 28 is sized and dimensioned to form a pressure barrier for a liquid disposed in the microchannel. One of ordinary skill in the art will be able to determine a suitable size and dimension of the stopper hole to create the pressure barrier. The stopper hole 28 acts as a stop for the meniscus of liquid filling the microchannel, such that the liquid plug 13 formed by the first liquid 4 extends only in one direction along
30 the length of the microchannel 3, away from the stopper hole 28.

 According to yet another embodiment, the cross-sectional dimensions of the microchannel 3 may be varied locally to affect the pressure within the microchannel

interior. For example, the microchannel may be narrowed or widened at certain locations to increase or decrease the capillary forces acting on a fluid in the microchannel interior. One of ordinary skill in the art will be able to determine a suitable cross-sectional dimension to achieve a desired pressure within the microchannel interior.

Alternatively, as shown in Figure 6, the microchannel 3' includes two fluid interface ports 17a and 17b, two stopper holes, 28a and 28b, and a vent hole 8 disposed between the two fluid interface ports 17a and 17b to allow for filling of the microchannel 3' with a plurality of different liquids. A first liquid 4 is introduced into the interior of the microchannel through the first fluid interface port 17a. The first stopper hole 28a causes the first liquid to extend along the microchannel towards the vent hole 8. A second liquid 4' is introduced into the interior of the microchannel through the second fluid interface port 17b and extends along the microchannel towards the vent hole 8, due to the presence and location of the second stopper hole 28b. Air in the microchannel is released through the vent hole 8.

After filling the microchannel via a fluid interface port 17, such as a filling hole disposed in the side wall of the microchannel, the fluid interface port may be closed to prevent leakage of the fluid from the microchannel. According to the embodiment shown in Figure 7a, the fluid interface port 17 is closed by dispensing drops of encapsulant 21a onto the fluid interface port 17. The encapsulant drops form a cap 21 and effectively close the microchannel 3. Alternatively, as shown in Figure 7b, the microchannel 3 may be closed after filling by adhering a closing layer 41 to the microchannel 3 to cover the fluid interface port 17.

According to another embodiment, as shown in Figure 8, the fluid interface port 17 may be utilized to provide a pumping mechanism to induce movement of liquid through the microchannel. As illustrated, the fluid interface port 17 may be disposed adjacent to a closed or open end of the microchannel 3. The introduction of droplets into the microchannel through the fluid interface port results in movement of liquid through the microchannel. This movement corresponds to the frequency of the drops introduced to the hole. The movement of liquid induced by the introduction of droplets

through the filling hole can be applied in many microfluidic applications as an accurate pumping and/or dosing mechanism. Those of ordinary skill will readily recognize that the microchannel can employ a hydrophobic patch or a stopper hole to induce liquid movement in a selected direction or any suitable means for conveying liquid through the
5 microchannel.

According to another aspect of the invention, a second fluid sample can be introduced to the microchannel 3 through the same or different fluid interface port 17, after the microchannel is filled with the first liquid 4. Figure 9a is a side view of a
10 microchannel 3 according to an illustrative embodiment of the invention including a fluid interface port 17 formed in the side wall 16 of the channel and showing a droplet generating system 18 for forming droplets of the second fluid sample to be introduced into the microchannel 3. The fluid interface port 17 provides a direct interface between the microchannel interior and the exterior. According to the present invention, the
15 interface between a first liquid 4 in the microfluidic system and a surrounding gas phase is defined by the local absence of a solid wall in the microchannel, rather than a separate channel or reservoir structure.

According to one aspect, the virtual wall 15 formed in the port 17 can be used as
20 a sample introduction port for introducing the second liquid into the first liquid 4 in the form of liquid droplets. A second liquid 19a can be directly injected into the first liquid 4 within microchannel 3 through the virtual wall 15 without requiring an intermediate structure, such as a sample introduction channel or a sample reservoir. According to the illustrative embodiment, the second liquid is introduced by forming a droplet 19b of the
25 second liquid 19a and directing the droplet towards the virtual wall 15 with an appropriate speed and direction, indicated in Figure 9a by velocity vector V , so as to traverse the virtual wall 15 and enter the interior of the microchannel.

The liquid droplets may be formed and dispensed using any suitable droplet
30 forming system 18, such as the droplet dispensing systems described in U.S. Provisional Patent Application Attorney Docket Number CVZ-002-1 filed September 25, 2001 and entitled "Two-Pin Liquid Sample Dispensing System", the contents of which are herein incorporated by reference, and U.S. Provisional Patent Application Number 60/325,040

entitled “Droplet Dispensing System”, the contents of which are herein incorporated by reference.

According to the illustrative embodiment, the lateral dimensions of the fluid interface port 17 are substantially identical to or less than the diameter of the microchannel 3, whilst the diameter of the illustrated droplet 19b is smaller than the lateral dimensions of the fluid interface port 17. The fluid interface port 17 has a dead volume that is substantially smaller when compared to conventional fluid interface ports, such as a well or a sample introduction channel. As used herein, “dead volume” refers to the volume of liquid retained in the fluid interface port 17 (i.e. the volume of liquid the fluid interface port holds that is not flushed through the fluid interface port by the flow field of the first liquid 4 through the microchannel). The total volume of the fluid interface port 17 is defined by the area of the aperture formed in the side wall and the thickness of the side wall 16. The volume of the first liquid 4 filling the fluid interface port defines the dead volume. According to the illustrative embodiment, the fluid interface port has a dead volume that is less than about one nanoliter and preferably less than one picoliter, and most preferably about zero. Preferably, the dead volume is less than the volume of liquid sample that is injected through the fluid interface port 17.

The size of the aperture and the hydrophobicity of the fluid interface port determine the size of the dead volume. For example, the microchannel shown in Figure 9a has zero dead volume i.e. no liquid is retained in the fluid interface port 17 and a sample injected through the port 17 directly enters the microchannel interior. According to other embodiments, the first liquid may partially or totally fill the aperture, and the dead volume may be a non-zero, but substantially small, value. The dead volume also depends in whether the meniscus 15 bulges up or down, a factor that is controlled by the hydrophobicity of the port 17, the properties of the liquid filling the microchannel 3 and the size of the aperture forming the port 17.

The relatively small dead volume provided by the virtual wall 15 results in a direct fluid interface allowing direct injection of a precise volume of sample into the interior of the microchannel 3 from the exterior of the microchannel. The ability to directly inject sample into the microchannel due to the low dead volume of the fluid

interface port 17 provides improved control over the amount of sample that is injected into the microchannel, allows efficient use of sample, and significantly reduces waste of the sample. Furthermore, the direct injection provided by the very small dead volume reduces or prevents cross-contamination between different samples and allows a third liquid to be directly injected into the system immediately after a second liquid without requiring flushing of the fluid interface port. Conversely, in conventional microfluidic systems employing a sample introduction channel, sample well or sample reservoir for introducing a fluid sample to a microchannel, the dead volume is significantly large relative to the size of the microchannel. In order to introduce a fluid sample into the microchannel interior, the fluid sample must first pass through the dead volume. A larger dead volume leads to dispersion of the sample, a time delay between the time of injection and the time when the sample enters the microchannel, injection inefficiency, potential cross-contamination between different samples and difficulty controlling the amount of sample that actually reaches the microchannel. These problems are avoided or reduced by the use of the fluid interface port 17 forming a virtual wall 15 according to the illustrative embodiment.

Figure 9b shows a cross-sectional view perpendicular to the microchannel 3 at the location of fluid interface port 17, illustrating the process of introducing the second liquid 19a into the first liquid 4 through the virtual wall 15. As illustrated in Figure 9b, the droplet generating system 18 comprises a droplet carrying element for carrying the droplet. According to the illustrative embodiment, the droplet carrying element 180 comprises a pin, as described in U.S. Provisional Patent Application Attorney Docket Number CVZ-002-1 filed September 25, 2001 and entitled "Two-Pin Liquid Sample Dispensing System", and U.S. Provisional Patent Application Number 60/325,040 entitled "Droplet Dispensing System", for introducing the droplet to the aperture by contacting the virtual wall 15.

Figure 9c shows a cross-sectional view of the microchannel 3 immediately after injection of the second liquid 19a in the first liquid 4. As illustrated, the second liquid 19a forms a well defined plug 14 in the first liquid 4. According to an alternate embodiment, the second liquid dissolves, merges or mixes into the first liquid. After

introduction via the virtual wall, the second liquid 19a is transported through the microchannel by the first liquid 4.

According to one embodiment of the invention, illustrated in Figure 9d, the second liquid, which is introduced into the microchannel 3 via the virtual wall, is immiscible with the first liquid. Figure 9d shows a cross-sectional view of the microchannel 3 immediately after injection of the immiscible second liquid 19a in the first liquid 4. After penetrating the virtual wall 15, a substantially spherical, micelle-like liquid volume 71 of the second liquid is formed in the first liquid 4. As both liquids are immiscible with each other, this liquid volume 71 remains confined and can be separately transported along the microchannel 3.

The illustrative mode of liquid injection into a microfluidic system via a virtual wall and consecutive handling is particularly preferable for performing a liquid-liquid extraction. Liquid-liquid extraction is a well-known technique, widely used in many chemical analysis and synthesis steps, especially during drug discovery. In liquid-liquid extraction, two immiscible liquids are brought in intimate contact to allow the extraction of specific components from the liquid containing a specific substance (i.e. the source liquid) into the extraction medium (i.e. the target liquid). A suitable example of liquid-liquid extraction is the extraction of a water-soluble substance synthesized in an organic solvent, whereby said solvent is immiscible with water. The organic solvent containing the water-soluble synthesis product of interest is mixed with water to form small micelle-like droplets of solvent in the water phase. The water soluble substance diffuses out of the solvent and is collected in the water phase. The water phase can be re-collected after a predetermined time, due to the immiscible properties of the two substances. In this manner, the water soluble substance is thus extracted from the organic liquid phase. Of key importance is the total contact surface between both liquids. A larger exchanging surface, provided by the shape of the droplets, results in a faster extraction process.

The microfluidic system of the present invention may be utilized to perform a liquid-liquid extraction between a water soluble substance and an organic liquid phase, which is immiscible with water, as described below. To perform a liquid-liquid

extraction between a water soluble substance and an organic liquid phase, the illustrative microchannel 3 is filled with a suitable first liquid 4, which is, according to the illustrative embodiment, an appropriate aqueous solution. The first liquid 4 forms a virtual wall 15 at the opening 17 disposed in the side wall of the microchannel. Droplets 19b of the organic phase containing the substance are formed and injected into the first liquid 4 through the virtual wall 15. After the droplets 19b traverse the virtual wall, micelle-like liquid volumes 71 are formed in the microchannel 3, which, due to their very small size, have a relatively very large exchange surface area. Consequently, the water soluble substance initially present in the micelle-like liquid volumes 71 is extracted into the first liquid 4 and is available for further processing. To concentrate the substance in a consecutive step, the extracted micelle-like liquid volumes 71 are separated from liquid 3 by a suitable separating technique as known in the art, including, but not limited to, electrophoresis, dielectrophoresis, gravitational or body forces, capillary forces and special selective sieves.

According to an alternate embodiment, shown in Figure 9e, the fluid interface port 17 disposed in the microchannel side wall 16 and forming a virtual wall 15 may have any suitable shape, such as a cylindrical or conical shape, having a suitably low dead volume for providing direct access to the microchannel interior. According to one embodiment, the inner wall 63 of the fluid interface port 17 is formed of or coated with a material that is repellant for the first liquid 4 to repel the first liquid from the opening 17. According to a preferred embodiment, the inner wall 64 of the microchannel 3 is attractive for the first liquid 4, to retain the first liquid inside the microchannel. The liquid repellent section in the fluid interface port 17 prevents liquid from leaking out of the microfluidic system and ensures the repeatable formation of a virtual wall 15 in the fluid interface port 17 when the microchannel is filled with liquid. The use of an inner wall 64 that is attractive for the first liquid 4 further enhances automatic, passive capillary filling of the microchannel 3 via the port 17, as described above, or by providing the first liquid 4 at one end of the microchannel 3. As a result of capillary forces, the microchannel 3 may be automatically filled without requiring application of external energy or pressure sources, such as pumps or pressure chambers.

Figure 9f illustrates an embodiment where the microchannels and virtual wall 15 are covered with a covering layer 66. According to the illustrative embodiment, the covering layer 66 comprises a liquid layer that is immiscible with the first liquid 4 in the microchannel. The covering layer prevents the evaporation of the first liquid 4 from the microchannel through the opening 17, while still allowing the injection of a second liquid, such as liquid 19a, into the microchannel through the covering layer 66 and the virtual wall 15.

According to an alternate embodiment, as shown in Figure 9g, the fluid interface port in the microchannel is formed by an array 72 of openings 17, each forming a virtual wall 15 upon filling of the microchannel 3 with the first liquid 4. The virtual walls 15 in the array 72 are disposed in close proximity to each other, thereby allowing the injection of liquid via a wicking process, as illustrated in Figure 9h. To introduce a second liquid into the microchannel, as shown in Figure 9h, a selected amount of the second liquid 19a is deposited on top of the array 72, such that the capillary forces wick the second liquid into the microchannel 3. According to a preferred embodiment, the inner walls 63 of the fluid interface port 17 are rendered repellant to the first liquid 4 whilst the outer surfaces 65 of the fluid interface ports 17 preferably are rendered attractive to the second liquid 19a. The use of an array of openings to form an array of virtual walls reduces the necessity and criticality of precisely targeting the droplets 19b towards a particular virtual wall. The droplets need only to be aimed in the direction of the array, allowing capillary forces to pull droplets into the channel interior. The velocity and direction of the propelled droplets are also not as important to achieve injection of the sample into the microchannel 3.

25

According to yet another embodiment of the invention, a plurality of openings are disposed in the side wall of the microchannel to allow for the introduction or ejection of liquid via a virtual wall at a plurality of locations in the microchannel. For example, as shown in Figure 10a, the microchannel can include multiple fluid interface ports 17a, 17b positioned across or along the width of the microchannel 3 to define a plurality of virtual walls to allow for simultaneous introduction of a plurality of liquids. In this manner, an increased volume of liquid may be immediately injected into the microchannel 3 via the plurality of virtual walls. The use of a plurality of virtual walls

across the microchannel width further allows for simultaneous introduction and mixing of a plurality of different liquids. As shown in Figure 10a, the microchannel includes a first liquid 4. A second liquid 19a may be introduced via a first virtual wall 15a.

Simultaneously, a third liquid 190a may be introduced via a second virtual wall 15b.

- 5 The second liquid 19a and the third liquid 190a mix together with the first liquid 4, as illustrated by the diffusion profiles of the liquids.

- 10 Alternatively, as shown in Figure 10b, the microchannel 3 may include a plurality of virtual walls disposed along the length of the microchannel to allow for sequential introduction of liquids into the microchannel, or ejection of a liquid from the microchannel along different locations in the fluid flow path.

- 15 The illustrative microfluidic system 10 employing a virtual wall 15 in a fluid interface port may be utilized with a sample introduction system for forming and guiding a droplet into a microchannel via a virtual wall. Figure 11a illustrates the microfluidic system 10 employing a suitable sample introduction system 67 for guiding a charged droplet 19d of a selected sample into a microchannel 3a of selected interest. The illustrated sample introduction system 67 includes a droplet generator 18 for forming droplets of a selected liquid, a droplet charging circuit 53 for selectively
- 20 charging a droplet, and a droplet guiding system 150, comprising a ground electrode 54 and a plurality of electrically controlled deflection plates 56, 57, for establishing an electrostatic field to direct the charged droplets to a selected location. The illustrative microfluidic system 10 can be coupled to electronics for controlling the formation and guidance of the droplet to a selected microchannel.

25

- 30 The droplets are generated by the droplet generator 18 having a nozzle assembly 70. The nozzle assembly 70 ejects liquid and forms individual droplets of the liquid at a breaking off point 62. The droplet charging circuit 53 is pre-programmed and a corresponding electrode 52 is positioned within the nozzle assembly to charge a pre-selected droplet with either a positive or negative charge at the breaking off point 62. Surrounding the breaking off point 62 of the droplet formation is a ground electrode 54. After breaking off and passing the ground electrode 54, the charged droplet 19c travels through an electrostatic field established by the first electrically controlled deflection

plate 56 and the second electrically controlled deflection plate 57. A plate-charging circuit 55 is associated with each plate and controls the polarities thereof to provide proper electrical charging to the respective deflection plates. As shown in FIG. 11a, the droplet 19d is charged positively and is deflected towards a virtual wall 15 disposed in the selected microchannel 3a by negatively charging the first plate 56 and positively charging the second plate 57. By controlling the charge on individual droplets with droplet charging circuit 53 as well as controlling the electric field between the first plate 56 and the second plate 57, droplets can be guided and effectively targeted to a particular channel to effect pre-programmed chemical experiments.

10

Figure 11b is a cross-sectional view of a plurality of microchannels 3 with associated fluid interface ports 17 employing a different charging technique according to an alternate embodiment of the present invention. In the embodiment shown in Figure 11b, the droplet guiding system 150 comprises an electrode 58 for each microchannel in the system and a channel charging circuit 59 for charging the microchannels. Each microchannel 3 includes a corresponding electrode 58 for enhanced targeting of the droplets by selectively charging the corresponding microchannel. The electrode 58 is connected to the channel charging circuit 59, associated with the droplet charging circuit 53 shown in Figure 11a, for generating a selected charge in each of the microchannels 3. The channel charge interacts with the charged droplets to guide or steer the charged droplet 19d towards a respective microchannel 3a. As seen in Figure 11b, the droplet 19d is positively charged whilst a selected microchannel 3a is charged negatively, thereby resulting in an attractive force between the positively charged droplet 19d and the virtual wall 15 of the negatively charged microchannel 3a. Guiding is enhanced by charging neighboring microchannels 3b and 3c with identical sign as the selected droplet 19d, which consequently repel the positively charged droplet 19d towards the selected microchannel 3a.

15

20

25

30

Figure 11c shows an alternate approach to enhance targeting of a charged droplet 19d into a selected microchannel 3a of a plurality of microchannels 3, according to the present invention. In the embodiment shown in Figure 11c, the droplet guiding system 150 comprises a plurality of targeting electrodes 61, each associated with a corresponding fluid interface port or microchannel. The fluid interface ports and

corresponding microchannels are charged by a targeting electrode charging circuit 61 to result in a force towards the virtual wall 15 of the selected microchannel 3a. As seen in Figure 11c, the selected droplet 19d is positively charged whilst the targeting electrode 61 associated with the selected corresponding microchannel 3a is charged negatively to guide the selected droplet 19d into a selected corresponding microchannel 3a via the virtual wall 15. Guiding is enhanced by charging a neighboring targeting electrode 61 with an identical sign as the selected droplet 19d to repel the droplet away from the neighboring microchannels 3b, 3c and towards the selected microchannel 3a.

According to an alternate embodiment of the invention, the droplet guiding system 150 may comprise a machine vision system that can employ fiducial marks on one or more components of the system. One skilled in the art will recognize that any suitable droplet guiding system for directing a droplet towards a virtual wall may be utilized in accordance with the teachings of the invention.

According to the present invention, the fluid interface port 17 of the microfluidic system 10 can optionally be utilized as a bi-directional fluidic interface for the microchannel. In addition to providing an interface for introducing a sample to a microchannel, the illustrative virtual wall formed in the microchannel 3 filled with the first liquid 4 may also be utilized as an ejection port for ejecting fluid from the microchannel. Figures 12a through 12d show a cutaway view of a microchannel 3 in which a fluid interface port 17 disposed in a side wall of the channel can be used as an ejection port. The port 17 forms a virtual wall to allow the ejection of the first liquid 4 from microchannel 3. A suitable ejector 108 is provided in communication with the microchannel to effect ejection of the first liquid through the virtual wall 15. One skilled in the art will recognize that the ejector 108 may comprise any suitable device or system for ejecting a droplet from the microchannel via the virtual wall fluid interface port.

According to the illustrated embodiment shown in Figure 12a, the ejector comprises a first electrode 34 disposed in the first liquid 4 and an electrospray electrode 32 positioned in the vicinity of the port 17. A voltage generator 31 is connected to the first electrode 34 and the electrospray electrode 32 for applying a potential difference

and generating an electric field between the electrospray electrode 32 and the first liquid 4. The electric field generated by the voltage generator 31 between the electrodes results in an attractive force on the first liquid 4, thereby effectively pulling the first liquid 4 out of the microchannel through the virtual wall 15 in the form of a droplet 33.

- 5 The virtual wall and microchannel arrangement shown in Figure 12a can also be used to receive droplets of a second liquid through the virtual wall, as discussed above, by removing the electric field, thereby achieving a bi-directional interface.

Figure 12b shows another embodiment of the microfluidic system 10 of the present invention suitable for ejecting the first liquid 4 from the microchannel 3. According to this embodiment, the ejector comprises a pressure pulse generator 51 in communication with the first liquid 4 in the microchannel 3. The pressure pulse generator 51 applies a pressure pulse having a selected amplitude, frequency and duration to the fluid 4 to effectively eject the first liquid 4 through the virtual wall to form a droplet 33. The pressure pulse generator 51 can be any suitable structure for generating a pressure pulse within the microchannel 3 and can include a piezoelectric element, an electromagnetic actuator, a heater, an electrostatic actuator, comprising electrodes that move under the influence of an applied voltage, an electrophoretic pressure actuator, comprising electrodes in channel on which a voltage pulse is applied, pressurized gas or any other suitable pressure pulse generator.

The pressure pulse generator 51 can either be integrated at least partly within the microchannel 3 or can be fully external and working with the channel, such as a rod-like moving actuator tapping locally on the channel.

25 According to another embodiment, shown in Figure 12c, a gas pressurizer 51a is utilized to eject the liquid from the microchannel. According to the illustrative embodiment, the gas pressurizer 51a comprises a pressurized gas tank, which applies pressure via a fast valve. A second fluid interface port 17b forming a second virtual wall 15b can be formed in the microchannel 3. The second virtual wall 15b is substantially coaxially aligned with the first virtual wall formed in the first fluid interface port 17. The second, coaxial virtual wall 15b is in communication with the gas pressurizer 51a which generates a gas pressure pulse having a selected amplitude,

frequency and duration as to effectively eject the first liquid 4 through the first virtual wall 15 in the form of a droplet 33. During the ejection process, the second virtual wall 15b is displaced inwards towards the first liquid 4 so as to form the droplet 33.

5 According to an alternate embodiment, as shown in Figure 12d, the ejector comprises a heater 51b disposed in the microchannel 3 along the side wall. The heater 51b locally heats the first liquid 4 in order to form a droplet. The heating of the first liquid results in a quickly growing gas vapor bubble 51c, which effectively ejects the droplet 33 from the microchannel 3 via the virtual wall 15. The heater may comprises a
10 heated spot, an electrical heater, an optically induced heater or any other suitable heater.

 According to yet another embodiment of the invention, the virtual wall 15 formed in the side wall 16 of the microchannel 3 is utilized to optically analyze the interior of the microchannel. Figure 13a shows an embodiment of the invention where
15 the first liquid 4 disposed in the microchannel is optically inspected by a light beam 27 focused by an optical element 26. The light beam 27 is co-axially aligned with the fluid interface port 17 in the side wall as to directly penetrate the first liquid 4 without impinging upon the channel wall 16 opposite the port 17. The optical element 26 can be any suitable lens or prism. A suitable detector 68 is disposed adjacent to the virtual wall
20 15 to monitor and analyze the liquid in the microchannel 3. In an alternate embodiment, a plurality of fluid interface ports 17 and 17b are at disposed in the side wall at right angles to each other and scattering, rather than absorption, is analyzed.

 According to an alternate embodiment for optically analyzing the first liquid 4
25 through the virtual wall 15, a second virtual wall 15b is disposed in the microchannel 3. Figure 13b shows an embodiment for optical analysis of first liquid 4 in microchannel 3, in which a first fluid interface port 17 forming a first virtual wall 15 is disposed on one side of the microchannel 3 and a second fluid interface port 17b forming a second virtual wall 15b is disposed on the opposite side of microchannel 3, such that the first virtual
30 wall 15 and the second virtual wall 15b are substantially co-axially arranged. The light beam 27 passing through and focused by the optical element 26 is substantially co-axially positioned relative to the first virtual wall such that the light beam 27 directly penetrates the first liquid 4 through the port 17, and after traveling through the first

liquid 4 exits on the opposing side of the microchannel via the second virtual wall 15b. The light passing through the second port 17b can be collected, focused or collimated by a second optical element 26a in communication with an optical detector 68 to monitor and analyze the liquid in the microchannel 3. Such optical detection means are ideally
5 suitable for analyzing liquids containing compounds that are intrinsically colored or fluorescent, or that are labeled with an optically detectable moiety as described elsewhere herein. Alternatively, mass spectrometry may be used as a detection means when a microfluidic chip of the present invention is interfaced with a mass spectrometer.

10 According to one application of the present invention, a microfluidic system employing an aperture sized and dimensioned to form a virtual wall as a fluid interface port may be utilized to purify or filter a sample. For example, the illustrative arrangement may be utilized to purify a DNA sample by separating contaminants from the DNA fragments in the sample. As shown in Figure 14, a microchannel 3 having a
15 fluid interface port 17 formed in the side wall and defining a virtual wall is connected to a plurality of waste channels 136 and an outlet channel 137 formed at the intersection of the waste channels 136 and the microchannel main body 3. The microchannel 3 has an inlet 138 having a smaller diameter than the main body of the microchannel. The microchannel 3 is filled with a suitable washing medium 4 to effect separation of a
20 sample that is introduced via the virtual wall.

To achieve separation of a sample, such as the separation of a DNA sample from contaminants, a fluid flow is induced in the washing medium through the microchannel and the sample is injected into the flowing washing medium via the virtual wall 15. The
25 arrangement exploits diffusion to separate the different components of the sample. The larger molecules (i.e. the DNA fragments) in the sample and the smaller molecules in the sample (i.e. the contaminants) diffuse in the washing medium with different diffusion rates, which effectively separates the different components of the sample according to size. For example, the smaller molecules diffuse into the washing medium
30 faster than the larger molecules. The two sample streams, the residual sample stream containing the larger particles and the diffused sample stream containing the contaminants, are separated into the outlet channel 137 and the waste channels 136, respectively. The purified sample may pass through the outlet channel 137 for further

processing, or analysis. The waste channels 136 and the outlet channel 137 may be sized and positioned to receive a selected component. For example, the waste channels 136 are positioned a predetermined distance from the virtual wall 15 to receive the diffused smaller molecules and the outlet channel 137 is sized and positioned to receive the larger molecules.

Alternatively, the configuration shown in Figure 14 may be utilized to perform chemical manipulations, such as a chemical reaction, non-covalent binding, adsorption or absorption, antibody binding, nucleic acid or oligonucleotide binding or hybridization, ion pairing, ion exchange, chromatographic separation, receptor hormone interaction, enzyme activity antagonism or agonism, or other suitable reaction on an analyte. The present invention applies to a variety of liquid samples, including solutions of compounds, whole cells or cell lysates, enzymes, proteins or peptides, and particles. Accordingly, the invention also has applications in proteomics, genomics, chromatography, diagnostics, and drug discovery.

Alternatively, the illustrative configuration may be utilized to perform a labeling operation, where the virtual wall is utilized as an interface port for one of the reactants in the labeling scheme. To perform a labeling operation, a labeling fluid is run through the microchannel and a liquid containing a substance to be labeled is injected through the virtual wall. The mixing of the two liquids is relatively fast, achieving rapid labeling of the substance. According to one embodiment, the labeling can be performed before a separation step, such as described above. According to one embodiment, a filtration device may also be utilized to remove excess unreacted label after the labeling scheme.

Depending on the particular type of detection method employed, a wide variety of detectable labels may be used in applications of the present invention. Labels are commonly detectable by spectroscopic, photochemical, biochemical, immunochemical, or chemical means. The label is coupled directly or indirectly to a molecule to be detected (a product, substrate, enzyme, or the like) according to methods well known in the art, and for example, as reagents introduced onto a chip via a virtual wall formed in a side wall of a microchannel according to the illustrative embodiment of the present invention. For example, useful nucleic acid labels include fluorescent dyes, enzymes

(e.g., as commonly used in an ELISA), biotin, dioxigenin, or haptens and proteins for which antibodies, preferably monoclonal, are available. Other suitable labels include fluorescent moieties, chemiluminescent moieties, magnetic particles, and the like. Still other labeling agents include monoclonal antibodies, polyclonal antibodies, proteins, or other polymers such as affinity matrices, carbohydrates or lipids. Detection of labeled compounds may be by a variety of known methods, including spectrophotometric or optical tracking of fluorescent markers, or other methods which track a molecule based upon size, charge, molecular weight, or affinity. A detectable moiety can be of any material having a detectable physical or chemical property. Such detectable labels have been well-developed in the field of gel electrophoresis, column chromatography, spectroscopic techniques, and the like, and in general, labels useful in such methods can be applied to the present invention. Thus, a label is any composition detectable by spectroscopic, photochemical, biochemical, immunochemical, electrical, optical thermal, or chemical means; and such label may be bound covalently to the molecules of interest (e.g., reaction of amine-containing compounds with ninhydrin) or non-covalently (e.g., reaction of a compound with a labeled antibody). Useful labels in the present invention include fluorescent dyes (e.g., fluorescein isothiocyanate, Texas red, rhodamine, and the like), enzymes (e.g., LacZ, CAT, horse radish peroxidase, alkaline phosphatase and others, commonly used as detectable enzymes, either as marker products or as in an ELISA), nucleic acid intercalators (e.g., ethidium bromide) and colorimetric labels such as colloidal gold or colored glass or plastic (e.g. polystyrene, polypropylene, latex, etc.) beads. Fluorescent labels are particularly preferred labels when optical detection means are employed. Preferred labels are typically characterized by one or more of the following: high sensitivity, high stability, low background, low environmental sensitivity and high specificity in labeling.

Several labels comprising fluorescent moieties are known, including 1- and 2-aminonaphthalene, p,p'-diaminostilbenes, pyrenes, quaternary phenanthridine salts, 9-aminoacridines, p,p'-diaminobenzophenone imines, anthracenes, oxacarbocyanine, merocyanine, 3-aminoequilenin, perylene, bis-benzoxazole, bis-p-oxazolyl benzene, 1,2-benzophenazin, retinol, bis-3-aminopyridinium salts, hellebrigenin, tetracycline, sterophenol, benzimidazolylphenylamine, 2-oxo-3-chromen, indole, xanthen, 7-hydroxycoumarin, phenoxazine, calicylate, strophanthidin, porphyrins, triarylmethanes

and flavin. In some cases, the amino acid tryptophan, which is either part of a peptide or protein of interest (i.e., it is endogenous to that peptide or protein) or which is added to said protein or peptide, may be used as a fluorescent label. Individual fluorescent reagent compounds which may be used in accordance with the invention, or which can

5 be modified to incorporate such functionalities include, e.g., dansyl chloride; fluoresceins such as 3,6-dihydroxy-9-phenylxanthhydrol; rhodamineisothiocyanate; N-phenyl 1-amino-8-sulfonatonaphthalene; N-phenyl 2-amino-6-sulfonatonaphthalene; 4-acetamido-4-isothiocyanato-stilbene-2,2'-disulfonic acid; pyrene-3-sulfonic acid; 2-toluidinonaphthalene-6-sulfonate; N-phenyl-N-methyl-2-aminoaphthalene-6-sulfonate;

10 ethidium bromide; stebrine; auromine-0,2-(9'-anthroyl)palmitate; dansyl phosphatidylethanolamine; N,N'-dioctadecyl oxacarbocyanine: N,N'-dihexyl oxacarbocyanine; merocyanine, 4-(3'pyrenyl)stearate; d-3-aminodesoxy-equilenin; 12-(9'-anthroyl)stearate; 2-methylantracene; 9-vinyanthracene; 2,2'(vinylene-p-phenylene)bisbenzoxazole; p-bis(2-(4-methyl-5-phenyl-oxazolyl))benzene; 6-

15 dimethylamino-1,2-benzophenazin; retinol; bis(3'-aminopyridinium) 1,10-decandiyl diiodide; sulfonaphthylhydrazone of hellibrienin; chlorotetracycline; N-(7-dimethylamino-4-methyl-2-oxo-3-chromenyl)maleimide; N-(p-(2-benzimidazolyl)-phenyl)maleimide; N-(4-fluoranthyl)maleimide; bis(homovanillic acid); resazarin; 4-chloro-7-nitro-2,1,3-benzooxadiazole; merocyanine 540; resorufin; rose bengal; and 2,4-

20 diphenyl-3(2H)-furanone. Many such fluorescent labeling reagents are commercially available from SIGMA chemical company (Saint Louis, Mo.), Molecular Probes, R&D systems (Minneapolis, Minn.), Pharmacia LKB Biotechnology. (Piscataway, N.J.), CLONTECH Laboratories, Inc. (Palo Alto, Calif.), Chem Genes Corp., Aldrich Chemical Company (Milwaukee, Wis.), Glen Research, Inc., GIBCO BRL Life

25 Technologies, Inc. (Gaithersburg, Md.), Fluka Chemica-Biochemika Analytika (Fluka Chemie AG, Buchs, Switzerland), and Applied Biosystems (Foster City, Calif.) as well as other commercial sources known to one of skill in the art.

Fluorescent labels are one preferred class of detectable labels, in part because by

30 irradiating a fluorescent label with light, one can obtain a plurality of emissions. Thus, a single label can provide for a plurality of measurable events. Detectable signal may also be provided by chemiluminescent and bioluminescent sources. Chemiluminescent sources include a compound which becomes electronically excited by a chemical

reaction and may then emit light which serves as the detectable signal or donates energy to a fluorescent acceptor. A diverse number of families of compounds have been found to provide chemiluminescence under a variety of conditions. One family of compounds is 2,3-dihydro-1,4-phthalazinedione. The most popular compound is luminol, which is a 5-amino compound. Other members of the family include the 5-amino-6,7,8-trimethoxy- and the dimethylamino[ca]benz analog. These compounds can be made to luminesce with alkaline hydrogen peroxide or calcium hypochlorite and base. Another family of compounds is the 2,4,5-triphenylimidazoles, with lophine as the common name for the parent product. Chemiluminescent analogs include para-dimethylamino and -methoxy substituents. Chemiluminescence may also be obtained with oxalates, usually oxalyl active esters, e.g., p-nitrophenyl and a peroxide, e.g., hydrogen peroxide, under basic conditions. Other useful chemiluminescent compounds are also known and available, including -N-alkyl acridinum esters (basic H_2O_2) and dioxetanes. Alternatively, luciferins may be used in conjunction with luciferase or lucigenins to provide bioluminescence. An illustrative example of on-chip labeling with a fluorescent moiety may be found in Harrison, et al., Sensors and Actuators B, vol. 33, pp. 105-09 (1996).

Other labeling moieties may be non-covalently bound to molecules of interest. Generally, a ligand molecule (e.g., biotin) is covalently bound to a polymer. The ligand then binds to an anti-ligand (e.g., streptavidin) molecule which is either inherently detectable or covalently bound to a signal system, such as a detectable enzyme, a fluorescent compound, or a chemiluminescent compound. A number of ligands and anti-ligands can be used. Where a ligand has a natural anti-ligand, for example, biotin, thyroxine, and cortisol, it can be used in conjunction with labeled, anti-ligands. Alternatively, any haptenic or antigenic compound can be used in combination with an antibody. Labels can also be conjugated directly to signal generating compounds, e.g., by conjugation with an enzyme or fluorophore. Enzymes of interest as labels will primarily be hydrolases, particularly phosphatases, esterases and glycosidases, or oxidoreductases, particularly peroxidases. Fluorescent compounds include fluorescein and its derivatives, rhodamine and its derivatives, dansyl, umbelliferone, etc. Chemiluminescent compounds include luciferin, and 2,3-dihydrophthalazinediones, e.g., luminol. Means of detecting labels are well known to those of skill in the art. Where

the label is a fluorescent label, it may be detected by exciting the fluorochrome with the appropriate wavelength of light and detecting the resulting fluorescence, e.g., by microscopy, visual inspection, via photographic film, by the use of electronic detectors such as digital cameras, charge coupled devices (CCDs) or photomultipliers and phototubes, and the like. Fluorescent labels and detection techniques, particularly microscopy and spectroscopy are preferred. Similarly, enzymatic labels are detected by providing appropriate substrates for the enzyme and detecting the resulting reaction product. Finally, simple colorimetric labels are often detected simply by observing the color associated with the label. For example, conjugated gold often appears pink, while various conjugated beads appear the color of the bead.

Figure 15 illustrates a microfluidic synthesis/analysis system 40 of an embodiment of the present invention for performing a microchemical process of a sample on a chip. The microfluidic synthesis/analysis system 40 comprises a first microchannel 3, a second microchannel 30 operating in parallel with the first microchannel, and a third microchannel 300 disposed at the end of the first and second microchannels and forming an intersection with the first and second microchannels for combining the output of the first microchannel 3 and the second microchannel 30. The microchannels 3, 30 and 300 include a plurality of fluid interface ports 17 forming virtual walls 15a-i disposed in the channel side walls for performing a multi-step chemical synthesis or analysis. The illustrative embodiment of the microfluidic synthesis / analysis system 40 serves as an example of the application of virtual walls 15 in microfluidic systems in which complex reaction schemes for synthesis (e.g. labeling, as described above) and analysis are to be performed in a highly parallel fashion. As shown, a large variety of chemical operations can be implemented by using a virtual wall 15 disposed in a side wall 16 of a microchannel 3.

The illustrated system 40 further includes a plurality of sample processors, illustrated as microreactors 43, 44, 45 and 46, disposed at selected locations in the microchannels 3, 30 and 300 for performing one or more reactions on a sample, such as a microchemical analysis or synthesis. According to the illustrative embodiment, the illustrated system is utilized to perform a separation of a sample. One skilled in the art will recognize that any suitable process may be performed on a sample, including, but

not limited to a reaction, filtration, dilution, mixing, binding and transporting, alone or in combination with other reactions. The specific arrangement shown in Figure 15 allows performing of the following Reactions 1-4:

5 Reaction 1: $A+B \rightarrow C$

Reaction 2: $D+E \rightarrow F$

Reaction 3: $C+F \rightarrow G$

Reaction 4: $G+H \rightarrow I$

10 In Reaction 1, substance A (e.g. a labeling reagent) reacts with substance B (e.g., a molecule of interest not otherwise conveniently detectable) to form substance C (e.g. a labeled conjugate). In Reaction 2, substance D reacts with substance E to form substance F. In Reaction 3, substances C and F react to form substance G. In Reaction 4, substances G and H react to form substance I. According to the illustrated
15 embodiment, Reaction 1 and Reaction 2 are carried out in parallel, sequentially followed by Reaction 3 and Reaction 4.

 In operation, a carrier liquid 4a is disposed in the microfluidic synthesis / analysis system 40 and a number liquids containing a specific chemical substance are
20 interfaced with the carrier liquid 4a via a plurality of virtual walls 15. The reaction products resulting from Reactions 1-4 are carried through the microfluidic synthesis/analysis system by carrier liquid 4a. Droplets 42a-i are formed of liquids respectively containing substances A-I listed in the above reaction scheme. The overall direction of flow of the carrier liquid 4 is indicated by arrows 41. The direction of
25 fluidic interfacing via the virtual walls 15 is indicated by arrows 47.

 To initiate the microfluidic process, a first liquid A 42a is introduced into the microfluidic system via a first virtual wall 15a, as indicated by droplet direction 47, and carried through the microchannel by the carrier liquid 4a. A second liquid B 42b is
30 added to the first microchannel 3 through a second virtual wall 15b disposed in the side wall of the microchannel downstream from the first virtual wall 15a, giving rise to a mixture of substances A and B present in carrier liquid 4a. Subsequently, the mixture passes through a first microreactor 43. The first microreactor 43 has appropriate

conditions (i.e. temperature, residence time, presence of catalytic materials etc.) to effect Reaction 1 and produce a third substance, liquid C, from the reaction of substances A and B. Liquid C is then carried downstream from the reactor 43 by the carrier liquid 4a. After completion of Reaction 1, portions of liquid C are ejected from the first
5 microchannel 3 through a third virtual wall 15c, disposed downstream of the first and second virtual walls 15a, 15c, in the form of a droplet 42c, as indicated by droplet direction 47. The ejected portion of liquid C may be subsequently stored, further processed or analyzed to determine the composition of the reacted liquid C.

10 In alternate embodiments of the invention, one or more of the sample processors 43, 44, 45 or 46 may comprise a separation means, rather than a reaction means such as a microreactor. A separation means is typically a chromatography column, preferably a chromatography column. A microfluidic system including a chromatography column may be used to perform a separation of a mixture applied, for example, via virtual wall
15 17, and then reacted with a labeling reagent in microreactor 45 with a reagent introduced through the virtual wall 15. In such a manner, compounds are labeled post-chromatographic separation. In like manner, a mixture may be introduced through a first virtual wall 15a and a labeling reagent through a second virtual wall 15b, followed by reaction in microreactor and subsequent separation in a chromatography column.
20 Capillary electrophoresis chromatography columns are particularly preferred separation means according to the invention. Such microfluidic CE columns are described in US Patents 6,159,353, 5,976,336, and 6,258,263, each of which are incorporated herein by reference. Alternatively, multiple separation means, optionally in parallel, may be employed by the present invention. For example, the microfluidic synthesis/analysis
25 system 40 may perform a first separation by capillary electrophoresis, and another separation based on a pH gradient.

In an alternate embodiment, a titration may be performed on-chip when a color change occurs upon reaction. Such a titration may be, for example, a pH titration, or a
30 titration of an enzyme with a chromogenic substrate or inhibitor.

A similar reaction process to the process that occurs in the first microchannel 3 takes place in the second channel 30 of the microfluidic synthesis / analysis system 40.

Respectively, liquid D 42d is introduced in carrier liquid 3b via a fourth virtual wall 15d. Downstream from the injection point for liquid D (i.e. virtual wall 15d), liquid E 42e is injected into the microchannel 3 via a fifth virtual wall 17e to form a mixture of substances D and E in the carrier liquid 4a. Further downstream, the mixture of substances D and E passes through a second microreactor 44, wherein Reaction 2 proceeds. After completion of Reaction 2, a portion of the resulting liquid F can be ejected from the second microchannel 30 via a sixth virtual wall 15f. The ejected portion of liquid F may be subsequently stored, further processed or analyzed to determine the composition of the reacted liquid F.

10

At the point of intersection of the first microchannel 3 and the second microchannel 30, the liquid C (42c) leaving the first microreactor 43 and the liquid F (42f) leaving the second microreactor 44 mix together and are subsequently carried through the third microchannel 300. The mixture of liquid F and liquid C enters the third microreactor 45, in which Reaction 3 proceeds and produces liquid G. A seventh virtual wall 15g disposed downstream from the third microreactor to allow for portions of liquid G leaving the third microreactor 45 to be ejected from microchannel 3 in the form of liquid droplets 42g. An eighth virtual wall 15h disposed further downstream from the seventh virtual wall liquid 15g is utilized to introduce substance H into the microchannel 300 in the form of liquid droplet 42h, resulting in a mixture of liquid G and liquid H. The G-H mixture enters a fourth microreactor 46, in which Reaction 4 ensues to form liquid I. Finally, portions of the resulting liquid I 42i leaving the fourth microreactor 46 are ejected from the microchannel 3 via a ninth virtual wall 15i disposed in the side wall of the microchannel 300 for analysis, storage and/or further processing of the liquid I.

According to the illustrative embodiment, the required concentrations of reactants A, B, D, E and H are precisely controlled by metering the size and number of droplets (19b). Moreover, by controlling the number of droplet 19b introduced in carrier liquid 4a, a specific dilution can precisely be obtained allowing the study of reactions 1-4 for different dilutions of reactants A, B, D, E and H. A suitable droplet dispensing system for forming droplets of suitable size is described in Provisional U.S. Patent Application 60/325,040. The use of a direct interface port formed by a virtual wall in

the side wall of the microchannel in the illustrative microfluidic synthesis / analysis system 40 allows precise control over the concentrations of liquids that are introduced into the system and significantly reduces waste while increasing efficiency.

5 The illustrative embodiment the microfluidic synthesis / analysis system 40 described above serves as an example of the application of a virtual wall 15 in microfluidic systems in which complex reaction schemes for synthesis and analysis are to be performed in a highly parallel fashion. As shown, a large variety of chemical operations can be implemented by using virtual wall 15 disposed in a side wall of a
10 microchannel. One skilled in the art will recognize that the invention is not limited to the illustrative embodiment and that any suitable size and number of microchannels, virtual walls, reactor types and numbers and sample types may be utilized in accordance with the teachings of the invention.

15 Figure 16 illustrates an alternate embodiment of the microfluidic system of the present invention. The system 10 includes a microchannel 3 including one or more fluid interface ports forming a virtual wall 15 and comprises a part of an electrokinetically operated system 22. In the electrokinetically operated system 22, an electric field is established to transport fluid through the microchannel 3. As illustrated a first electrode
20 5 and a second electrode 7 are disposed in or in fluid communication with the first liquid 4 in the microchannel 3. The first electrode 5 is disposed in a first well 6a located at a first end of the microchannel 3 and the second electrode 7 is disposed in a second well 6b located at a second end of the microchannel 3. The first well 6a and the second well 6b are in fluid communication with the first liquid 4 in the microchannel 3. A voltage
25 generator 12 generates a voltage between the first electrode 5 and the second electrode 7, which produces a substantially longitudinal electric field in the first liquid 4 in the microchannel 3. As shown in Figure 16, the longitudinal electric field is applied by bringing both ends of microchannel 3 in fluidic contact respectively with a first well 4 and a second well 6.

30

The illustrated port 17 is disposed in the side wall of the microchannel 3 and forms a virtual wall 15 allowing the introduction of a second liquid into a first liquid 4, according to the teachings of the invention. For example, the droplet generating system

18 forms a droplet 19a of the second fluid 19b. The droplet 19a is directed towards the port 17 via any suitable method, such as those described herein. Depending on the surface properties of the inner walls of the microchannel 3, the longitudinal electric field generated by the electrokinetic system 22 induces an electroosmotic liquid flow of the first liquid 4 in an axial direction through the microchannel 3, thereby substantially transporting the constituents present in the second liquid 19b in the axial direction through the microchannel.

The electrokinetically operated system 22 can include an optional detector 68 to provide for electrophoretic analysis of the constituents present in the second liquid 19b. The opening 17 disposed in the microchannel 3 has suitable properties, such as a selected diameter, length, and inner wall surface properties, to provide electrophoretic separation of the constituents of a liquid. A second liquid 19b to be analyzed is introduced to the microchannel 3 via the virtual wall 15 in the form of a droplet 19a generated by a droplet generating system 18. Constituents present in the introduced second liquid 19b are transported by a combination of electroosmotic flow and migration under the influence of the electric field applied with the voltage generator 12. After traveling a sufficient distance to result in electrophoretic separation of the liquid, the detector 68 detects and analyzes the individual constituents at the end of microchannel 3 by the detector 68. The detector 68 generates an electropherogram from which the composition of second liquid 19a can be determined. Those of ordinary skill will understand that the electrokinetic system of the invention can perform electroosmotic, electrophoretic, and dielectrophoretic techniques.

Figure 17 illustrates another implementation of an electrokinetically operated microfluidic system 50 according to the present invention comprising a plurality of parallel microchannels 3a-3h formed in a cartridge 73 in which a substrate 20 is disposed. The microchannels are formed by forming a network of half-open channel structures in the substrate and covering the half-open channels with a cover 20a to form the plurality of microchannels. The plurality of microchannels 3a-3h are disposed in the substrate in communication with a common first well 6a and a common second well 6b. The microchannels 3a-h include one or more fluid interface ports 17 defined by openings formed in the channel side wall that are sized and dimensioned to form virtual

walls when the microchannels are filled with a first liquid 4. A first electrode 5 connected to a voltage generator 12 is disposed in the common first well 6a and a second electrode connected to the voltage generator 12 is disposed in the common second well 6b to establish a substantially longitudinal electric field in the microchannel 3. Droplets 19b are generated by a droplet generator 18. The droplet generator 18 forms and propels the droplets towards a selected virtual wall 15 formed in a fluid interface port form in the side wall of a selected microchannel in a suitable direction and with a suitable velocity to introduce the droplet to the selected microchannel 3 via the opening 17. A detector 68 is positioned relative to the system 50 to monitor and detect the fluid in the microchannels 3a-3h.

In a preferred embodiment, the parallel implementation of an electrokinetically operated system 50 is applied as a highly parallel electrophoretic separation platform, capable of performing a large number of analyses per unit of time. The microchannels 3 disposed in the substrate 20 have suitable properties for electrophoretic separation (inner wall surface properties, diameter and length). The process of electrophoretic analysis of the constituents of droplet 19b is identical as described before. The electrokinetically operated apparatus 50 further includes a detector 68 for detecting and analyzing the individual constituents at the end of microchannels 3. The detector 68 generates an electropherogram from which the composition of second liquid 19a can be determined.

As shown, the illustrative electrokinetically operated system 50 comprises a compact structure, which allows a plurality of different reactions and processes to occur on a relatively small substrate 20. The use of openings forming virtual walls to define fluid interface ports in the side walls of the parallel microchannels 3a-3h allows direct interfacing of fluid with the microchannels, improves injection efficiency and provides easy control over the volume of liquid introduced into the system 50.

According to yet another application, the virtual walls may be utilized to interface a microfluidic system 181 with a mass spectrometer, as shown in Figure 18. For example, a sample may be injected into a microchannel 3 via a virtual wall 15 according to the teachings of the invention and the sample may then be separated into different components. After separation, the different components may be ejected from

the microchannel through a virtual wall 15 forming a fluid ejection port in the form of droplets. The droplets may be directed onto a suitable plate 185 for analysis with a mass spectrometer 186 or other robotic system. For example, the microfluidic system 181 may inject the separated samples onto a multi-well plate to form a multi-well array of the sample for analysis.

Figures 19a, 19b and 19c illustrate a method of manufacturing a microfluidic chip 190 having virtual wall interface ports for processing liquid samples. Figure 19a is an exploded view of a microfluidic chip 190 employing virtual wall fluid interface ports according to the teachings of the invention. Figure 19b is a top view of the microfluidic chip 190 of Figure 19a. Figure 19c is a cross-sectional side view of the manufactured microfluidic chip 190 of Figure 19a. As shown, a microchannel 3 with a virtual wall fluid interface ports 17 formed in the side wall of the microchannel may be manufactured with a three-layer "sandwich" construction. As shown, a complete microfluidic chip 190 having a microchannel 3, a first inlet 191 formed at a first end of the microchannel 3, an outlet 192 formed at a second end of the microchannel 3, and a fluid interface port 17 formed in a side wall along the length of the microchannel 3. The microfluidic chip shown in Figure 19 comprises a first planar sheet 193 having a recess 194 formed therein, a middle layer 197 including a channel 3 and an opening 17 and a second planar sheet 195. The opening 17 has dimensions between about 0.1 μm and about 200 μm and preferably between about 25 μm and about 125 μm and most preferably between about 50 μm and about 100 μm , so that a liquid disposed in the microchannel forms a virtual wall at the opening 17.

To manufacture the microfluidic chip 190, a portion of the first planar sheet 193 is removed to form the recess 194. Next, the middle layer is applied on top of the first sheet. Then, a portion of the middle layer 197 is removed to form the opening 17. Additional portions of the middle layer 197 are removed to form slits defining the microchannel, which are aligned with the recess. The second planar sheet 195 is applied to the middle layer 197, and a virtual wall access hole 170 is formed in the second planar sheet 195 prior to application or after application of the second planar sheet to the middle layer by removing a portion of the second planar sheet. The virtual wall access hole 170 is aligned with the opening 17 formed in the middle layer to provide access to

the microchannel. A low temperature bonding process may be utilized to assemble the three layers forming the chip.

According to the illustrative embodiment, the first and second planar sheets 193 and 195 comprise glass plates, though one skilled in the art will recognize that any suitable material may be used. Etching, powderblasting, or any suitable method may form the recess 197, channel 3, inlet 191, outlet 192 and the openings 17 and 170 forming the fluid interface port. According to an alternate embodiment, the recess 197, channel 3, inlet 191, outlet 192 and the openings 17 and 170 may be pre-formed in the layers, i.e. the layers may be molded to form the structures. According to the illustrative embodiment, the middle layer 197 is comprised of a photo patternable material, such as a photosensitive polymer applied by lamination. According to an alternate embodiment, the middle layer 197 of the microfluidic chip 190 also comprises a glass plate.

The use of glass plates to form the microfluidic chip 190 yields better optical detection of the microchannel 3 interior, as the top and bottom of the microchannel are formed by two parallel glass surfaces. In conventional round capillaries and also in etched channels on chip (also partly round surfaces) there is substantial light scattering due to the curved surfaces through which the light should pass. The glass surfaces are very flat and smooth to enhance the flow of fluid through the microchannel 3, and further facilitate and enhance electrophoresis. Furthermore, using glass substrates significantly reduces the cost of manufacturing the microfluidic chip 190.

According to one embodiment, a plurality of microchannels may be formed in the microfluidic chip, and can be configured to intersect with each other.

Figures 20a-c illustrate the steps of manufacturing a microchannel having a fluid interface port 17 defined by an opening suitable for forming a virtual wall according to an embodiment of the invention. Figure 20a is a cross-sectional view of a substrate 28 in which a first portion of an open channel 29 is formed. To form an enclosed microchannel, the substrate 28 is then covered with a cover 30, as shown in Figure 20b. Subsequently, at least a portion of the cover 30 is removed to form the fluid interface port 17 in microchannel 3, as shown in Figure 20c. As discussed, the fluid interface port

17 is sized and dimensioned to form a virtual wall when the microchannel is filled with a first liquid. In another embodiment the fluid interface port 17 is disposed in the cover 30 prior to bonding the cover 30 on top of substrate 28.

5 According to the illustrative embodiment, the substrate 30 and the cover 28 are formed of silicon, though one skilled in the art will recognize that any suitable material for forming a microchannel 3 in a microfluidic device or system may be utilized. For example, the microfluidic system may be made out of glass, plastic or any other suitable material. The microchannel 3 may be fabricated from a silicon wafer substrate 30 using
10 a standard photolithography etching process to fabricate the microchannel structures. A photolithography process may also be utilized to etch the fluid interface port 17 in the cover 28. One skilled in the art will recognize that alternative materials and manufacturing techniques, such as wet chemical etching, controlled vapor deposition, laser drilling, and the like, may be utilized.

15 Figures 21a-21c illustrate the steps of manufacturing a microchannel with a virtual wall interface port according to another embodiment of the invention. Figure 21a is a cutaway view of a substrate 28 in which a half open channel structure 29 is disposed. The substrate 28 is then covered with a first cover 30a on which a second
20 cover 30b is disposed, as shown in Figure 21b to form the enclosed microchannel 3. Subsequently, at least a portion of the first cover 30a and a portion of the second cover 30b are removed as to form the fluid interface port 17 in microchannel 3. As shown, the opening extends through the first cover 30a and the second cover 30b to form a fluidic interface between the interior of the microchannel 3 and the exterior of the
25 microchannel. In another embodiment the fluid interface 17 is formed in first cover 30a and second cover 30b prior to bonding of said first and second cover 30a and 30b to the top of the substrate 28.

 According to the illustrative embodiment, the substrate 30 and the first and
30 second covers 30a and 30b are formed of silicon, though one skilled in the art will recognize that any suitable material for forming a microchannel 3 in a microfluidic device or system may be utilized. For example, the microfluidic system may be made out of glass, plastic or any other suitable material. The microchannel 3 may be

fabricated from a silicon wafer substrate 30 using a standard photolithography etching process to fabricate the microchannel structures. A photolithography process is utilized to etch the fluid interface port 17 in the first and second covers 30a and 30b. One skilled in the art will recognize that alternative materials and manufacturing techniques, such as
5 wet chemical etching, controlled vapor deposition, laser drilling, and the like, may be utilized.

Figures 22a-22c illustrate the steps of manufacturing a microchannel having a virtual wall as a fluidic interface port according to an alternate embodiment of the
10 invention. In the embodiment shown in Figures 22a-22c, the opening forming the virtual wall is formed in a substrate having a half-open channel structure, rather than a cover for enclosing the half-open channel structure. Figure 22a shows an exploded view of a substantially planar first cartridge part 35 in which a half open channel structure 37 is disposed. A portion of the side wall of is removed from the half open channel
15 structure 37 in the substrate 35 to form a fluid interface port 17. A second cartridge part 36 is bonded to the top of the first cartridge part 35 to define a microchannel 3.

According to the illustrative embodiment, the first cartridge part 35 and the second cartridge part 36 are formed of silicon, though one skilled in the art will
20 recognize that any suitable material for forming a microchannel 3 in a microfluidic device or system may be utilized. For example, the microfluidic system may be made out of glass, plastic or any other suitable material. The microchannel 3 may be fabricated in the first cartridge part 36 using a standard photolithography etching process. A photolithography process is utilized to etch the fluid interface port 17 in the
25 side wall of the first cartridge part. One skilled in the art will recognize that alternative materials and manufacturing techniques, such as wet chemical etching, controlled vapor deposition, laser drilling, and the like, may be utilized according to the teachings of the present invention.

30 Figure 22b and Figure 22c show respectively a perspective view and a cutaway view of the resulting virtual wall 15 formed in the microchannel. As illustrated, the fluid interface port 17 formed in the microchannel is sized and dimensioned to form a virtual wall at the opening 17 when the microchannel is filled with a first liquid 4. The



virtual wall 15 allows fluidic interfacing with the microchannel as described above and is sized and dimensioned to retain liquid within the microchannel without adversely affecting liquid flow through the microchannel. Figures 19b and 19c illustrate the introduction of a droplet 19b of a second liquid 19a into a first liquid 4 present in the microchannel 3 via the virtual wall 15 formed within the opening 17. As shown, the droplet is propelled towards the virtual wall and traverses the virtual wall to enter the microchannel.

Figures 23a and 23b illustrate an alternate embodiment of the microchannel system of Figures 19-19c. Figure 23a shows an exploded view of a substantially planar first cartridge part 35 in which a half open channel structure 37 is disposed. A portion of the side wall of the cartridge part 35 is removed from the half open channel structure 37 to form an opening 17. A hydrophobic path 38 is disposed substantially opposite the opening 17 in the half open channel structure 37. A second cartridge part 36 is bonded to the top of the first cartridge part to define the microchannel 3. Upon filling of the microchannel 3, a first virtual wall 15 is formed at the opening 17 and a second virtual wall 15a is defined by the hydrophobic patch 38.

The hydrophobic patch enhances introduction of a second liquid into the microchannel. The hydrophobic patch 38 attracts first fluid 4, and prevents escape of the fluid through virtual wall. As illustrated in Figure 23b, a droplet of a second liquid is introduced into the microchannel via the virtual wall and drawn into the microchannel by the hydrophobic patch.

The use of a virtual wall in a microchannel side wall to create a bi-directional fluid interface for a microfluidic system provides significant advantages over conventional fluid interfaces. The fluid interface port comprising a virtual wall is relatively simple to manufacture, is compact, provides high ejection efficiency, does not adversely affect operation/flow, can be made bi-directional and is useful for a variety of applications. The illustrative embodiment eliminates the need for a separate structure, such as a channel or a reservoir and permits direct injection of a sample into a microchannel.



Exemplification of the Invention

Example 1: Virtual Wall microfluidic chip manufacturing and use

Microchannel structures having a fluid interface port were manufactured by
5 isotropic etching half-open channels, 100 micrometer in width, 50 micrometer in height
and a length of 20 mm, in a 1.1 mm thick glass wafer. A buffered hydrogen fluoride
(HF) solution was used as an etchant and photo patterned etchant resistant silicon nitride
mask layers were applied to define the microchannel areas to be etched. Access to the
channels was provided by powder blasting 1-mm diameter holes completely through the
10 glass wafer at both ends of each etched half-open microchannel.

A covering 50 micrometer thick layer of dry resist film (LAMINAR® 5000,
Shipley, Birkenfeld, Germany) was applied on top of the etched wafer. Fluid interface
ports were incorporated by photo patterning circular apertures of 50-150 micrometer in
15 the dry resist film whereby the apertures were aligned with and extended into the
underlying microchannels. Finally the wafer was diced in individual chips, which were
placed in a holder to connect the microchannel structures to external systems, such as
fluid pumps and electric power supplies.

20 The resulting microchannels were filled with an aqueous buffer solution (50mM
bi-carbonate buffer, pH 9.0). It was observed that the microchannels filled
automatically via capillary forces on the application of liquid to the fluid interface port.
Liquid drops having a diameter of about 50 micrometer were produced using a
piezoelectric-actuated drop dispenser system (MicroDrop GmbH, Norderstedt,
25 Germany). Drops were formed from a buffered solution containing a fluorescent dye
(50mM bi-carbonate buffer, pH 9.0, 1 mM fluoresceine) and were directed to a 100
micrometer diameter interface port. The injection process was monitored using an
inverted microscope under UV light irradiation to excite the fluorescent dye and obtain a
bright yellow-green color.

30

The present invention has been described relative to an illustrative embodiment.
Since certain changes may be made in the above constructions without departing from
the scope of the invention, it is intended that all matter contained in the above

description or shown in the accompanying drawings be interpreted as illustrative and not in a limiting sense.

It is also to be understood that the following claims are to cover all generic and
5 specific features of the invention described herein, and all statements of the scope of the invention which, as a matter of language, might be said to fall therebetween.

Having described the invention, what is claimed as new and protected by Letters Patent is:

10
11
12
13
14
15
16
17
18
19
20
21
22
23
24
25
26
27
28
29
30
31
32
33
34
35
36
37
38
39
40
41
42
43
44
45
46
47
48
49
50
51
52
53
54
55
56
57
58
59
60
61
62
63
64
65
66
67
68
69
70
71
72
73
74
75
76
77
78
79
80
81
82
83
84
85
86
87
88
89
90
91
92
93
94
95
96
97
98
99
100
101
102
103
104
105
106
107
108
109
110
111
112
113
114
115
116
117
118
119
120
121
122
123
124
125
126
127
128
129
130
131
132
133
134
135
136
137
138
139
140
141
142
143
144
145
146
147
148
149
150
151
152
153
154
155
156
157
158
159
160
161
162
163
164
165
166
167
168
169
170
171
172
173
174
175
176
177
178
179
180
181
182
183
184
185
186
187
188
189
190
191
192
193
194
195
196
197
198
199
200
201
202
203
204
205
206
207
208
209
210
211
212
213
214
215
216
217
218
219
220
221
222
223
224
225
226
227
228
229
230
231
232
233
234
235
236
237
238
239
240
241
242
243
244
245
246
247
248
249
250
251
252
253
254
255
256
257
258
259
260
261
262
263
264
265
266
267
268
269
270
271
272
273
274
275
276
277
278
279
280
281
282
283
284
285
286
287
288
289
290
291
292
293
294
295
296
297
298
299
300
301
302
303
304
305
306
307
308
309
310
311
312
313
314
315
316
317
318
319
320
321
322
323
324
325
326
327
328
329
330
331
332
333
334
335
336
337
338
339
340
341
342
343
344
345
346
347
348
349
350
351
352
353
354
355
356
357
358
359
360
361
362
363
364
365
366
367
368
369
370
371
372
373
374
375
376
377
378
379
380
381
382
383
384
385
386
387
388
389
390
391
392
393
394
395
396
397
398
399
400
401
402
403
404
405
406
407
408
409
410
411
412
413
414
415
416
417
418
419
420
421
422
423
424
425
426
427
428
429
430
431
432
433
434
435
436
437
438
439
440
441
442
443
444
445
446
447
448
449
450
451
452
453
454
455
456
457
458
459
460
461
462
463
464
465
466
467
468
469
470
471
472
473
474
475
476
477
478
479
480
481
482
483
484
485
486
487
488
489
490
491
492
493
494
495
496
497
498
499
500
501
502
503
504
505
506
507
508
509
510
511
512
513
514
515
516
517
518
519
520
521
522
523
524
525
526
527
528
529
530
531
532
533
534
535
536
537
538
539
540
541
542
543
544
545
546
547
548
549
550
551
552
553
554
555
556
557
558
559
560
561
562
563
564
565
566
567
568
569
570
571
572
573
574
575
576
577
578
579
580
581
582
583
584
585
586
587
588
589
590
591
592
593
594
595
596
597
598
599
600
601
602
603
604
605
606
607
608
609
610
611
612
613
614
615
616
617
618
619
620
621
622
623
624
625
626
627
628
629
630
631
632
633
634
635
636
637
638
639
640
641
642
643
644
645
646
647
648
649
650
651
652
653
654
655
656
657
658
659
660
661
662
663
664
665
666
667
668
669
670
671
672
673
674
675
676
677
678
679
680
681
682
683
684
685
686
687
688
689
690
691
692
693
694
695
696
697
698
699
700
701
702
703
704
705
706
707
708
709
710
711
712
713
714
715
716
717
718
719
720
721
722
723
724
725
726
727
728
729
730
731
732
733
734
735
736
737
738
739
740
741
742
743
744
745
746
747
748
749
750
751
752
753
754
755
756
757
758
759
760
761
762
763
764
765
766
767
768
769
770
771
772
773
774
775
776
777
778
779
780
781
782
783
784
785
786
787
788
789
790
791
792
793
794
795
796
797
798
799
800
801
802
803
804
805
806
807
808
809
810
811
812
813
814
815
816
817
818
819
820
821
822
823
824
825
826
827
828
829
830
831
832
833
834
835
836
837
838
839
840
841
842
843
844
845
846
847
848
849
850
851
852
853
854
855
856
857
858
859
860
861
862
863
864
865
866
867
868
869
870
871
872
873
874
875
876
877
878
879
880
881
882
883
884
885
886
887
888
889
890
891
892
893
894
895
896
897
898
899
900
901
902
903
904
905
906
907
908
909
910
911
912
913
914
915
916
917
918
919
920
921
922
923
924
925
926
927
928
929
930
931
932
933
934
935
936
937
938
939
940
941
942
943
944
945
946
947
948
949
950
951
952
953
954
955
956
957
958
959
960
961
962
963
964
965
966
967
968
969
970
971
972
973
974
975
976
977
978
979
980
981
982
983
984
985
986
987
988
989
990
991
992
993
994
995
996
997
998
999
1000
1001
1002
1003
1004
1005
1006
1007
1008
1009
1010
1011
1012
1013
1014
1015
1016
1017
1018
1019
1020
1021
1022
1023
1024
1025
1026
1027
1028
1029
1030
1031
1032
1033
1034
1035
1036
1037
1038
1039
1040
1041
1042
1043
1044
1045
1046
1047
1048
1049
1050
1051
1052
1053
1054
1055
1056
1057
1058
1059
1060
1061
1062
1063
1064
1065
1066
1067
1068
1069
1070
1071
1072
1073
1074
1075
1076
1077
1078
1079
1080
1081
1082
1083
1084
1085
1086
1087
1088
1089
1090
1091
1092
1093
1094
1095
1096
1097
1098
1099
1100
1101
1102
1103
1104
1105
1106
1107
1108
1109
1110
1111
1112
1113
1114
1115
1116
1117
1118
1119
1120
1121
1122
1123
1124
1125
1126
1127
1128
1129
1130
1131
1132
1133
1134
1135
1136
1137
1138
1139
1140
1141
1142
1143
1144
1145
1146
1147
1148
1149
1150
1151
1152
1153
1154
1155
1156
1157
1158
1159
1160
1161
1162
1163
1164
1165
1166
1167
1168
1169
1170
1171
1172
1173
1174
1175
1176
1177
1178
1179
1180
1181
1182
1183
1184
1185
1186
1187
1188
1189
1190
1191
1192
1193
1194
1195
1196
1197
1198
1199
1200
1201
1202
1203
1204
1205
1206
1207
1208
1209
1210
1211
1212
1213
1214
1215
1216
1217
1218
1219
1220
1221
1222
1223
1224
1225
1226
1227
1228
1229
1230
1231
1232
1233
1234
1235
1236
1237
1238
1239
1240
1241
1242
1243
1244
1245
1246
1247
1248
1249
1250
1251
1252
1253
1254
1255
1256
1257
1258
1259
1260
1261
1262
1263
1264
1265
1266
1267
1268
1269
1270
1271
1272
1273
1274
1275
1276
1277
1278
1279
1280
1281
1282
1283
1284
1285
1286
1287
1288
1289
1290
1291
1292
1293
1294
1295
1296
1297
1298
1299
1300
1301
1302
1303
1304
1305
1306
1307
1308
1309
1310
1311
1312
1313
1314
1315
1316
1317
1318
1319
1320
1321
1322
1323
1324
1325
1326
1327
1328
1329
1330
1331
1332
1333
1334
1335
1336
1337
1338
1339
1340
1341
1342
1343
1344
1345
1346
1347
1348
1349
1350
1351
1352
1353
1354
1355
1356
1357
1358
1359
1360
1361
1362
1363
1364
1365
1366
1367
1368
1369
1370
1371
1372
1373
1374
1375
1376
1377
1378
1379
1380
1381
1382
1383
1384
1385
1386
1387
1388
1389
1390
1391
1392
1393
1394
1395
1396
1397
1398
1399
1400
1401
1402
1403
1404
1405
1406
1407
1408
1409
1410
1411
1412
1413
1414
1415
1416
1417
1418
1419
1420
1421
1422
1423
1424
1425
1426
1427
1428
1429
1430
1431
1432
1433
1434
1435
1436
1437
1438
1439
1440
1441
1442
1443
1444
1445
1446
1447
1448
1449
1450
1451
1452
1453
1454
1455
1456
1457
1458
1459
1460
1461
1462
1463
1464
1465
1466
1467
1468
1469
1470
1471
1472
1473
1474
1475
1476
1477
1478
1479
1480
1481
1482
1483
1484
1485
1486
1487
1488
1489
1490
1491
1492
1493
1494
1495
1496
1497
1498
1499
1500
1501
1502
1503
1504
1505
1506
1507
1508
1509
1510
1511
1512
1513
1514
1515
1516
1517
1518
1519
1520
1521
1522
1523
1524
1525
1526
1527
1528
1529
1530
1531
1532
1533
1534
1535
1536
1537
1538
1539
1540
1541
1542
1543
1544
1545
1546
1547
1548
1549
1550
1551
1552
1553
1554
1555
1556
1557
1558
1559
1560
1561
1562
1563
1564
1565
1566
1567
1568
1569
1570
1571
1572
1573
1574
1575
1576
1577
1578
1579
1580
1581
1582
1583
1584
1585
1586
1587
1588
1589
1590
1591
1592
1593
1594
1595
1596
1597
1598
1599
1600
1601
1602
1603
1604
1605
1606
1607
1608
1609
1610
1611
1612
1613
1614
1615
1616
1617
1618
1619
1620
1621
1622
1623
1624
1625
1626
1627
1628
1629
1630
1631
1632
1633
1634
1635
1636
1637
1638
1639
1640
1641
1642
1643
1644
1645
1646
1647
1648
1649
1650
1651
1652
1653
1654
1655
1656
1657
1658
1659
1660
1661
1662
1663
1664
1665
1666
1667
1668
1669
1670
1671
1672
1673
1674
1675
1676
1677
1678
1679
1680
1681
1682
1683
1684
1685
1686
1687
1688
1689
1690
1691
1692
1693
1694
1695
1696
1697
1698
1699
1700
1701
1702
1703
1704
1705
1706
1707
1708
1709
1710
1711
1712
1713
1714
1715
1716
1717
1718
1719
1720
1721
1722
1723
1724
1725
1726
1727
1728
1729
1730
1731
1732
1733
1734
1735
1736
1737
1738
1739
1740
1741
1742
1743
1744
1745
1746
1747
1748
1749
1750
1751
1752
1753
1754
1755
1756
1757
1758
1759
1760
1761
1762
1763
1764
1765
1766
1767
1768
1769
1770
1771
1772
1773
1774
1775
1776
1777
1778
1779
1780
1781
1782
1783
1784
1785
1786
1787
1788
1789
1790
1791
1792
1793
1794
1795
1796
1797
1798
1799
1800
1801
1802
1803
1804
1805
1806
1807
1808
1809
1810
1811
1812
1813
1814
1815
1816
1817
1818
1819
1820
1821
1822
1823
1824
1825
1826
1827
1828
1829
1830
1831
1832
1833
1834
1835
1836
1837
1838
1839
1840
1841
1842
1843
1844
1845
1846
1847
1848
1849
1850
1851
1852
1853
1854
1855
1856
1857
1858
1859
1860
1861
1862
1863
1864
1865
1866
1867
1868
1869
1870
1871
1872
1873
1874
1875
1876
1877
1878
1879
1880
1881
1882
1883
1884
1885
1886
1887
1888
1889
1890
1891
1892
1893
1894
1895
1896
1897
1898
1899
1900
1901
1902
1903
1904
1905
1906
1907
1908
1909
1910
1911
1912
1913
1914
1915
1916
1917
1918
1919
1920
1921
1922
1923
1924
1925
1926
1927
1928
1929
1930
1931
1932
1933
1934
1935
1936
1937
1938
1939
1940
1941
1942
1943
1944
1945
1946
1947
1948
1949
1950
1951
1952
1953
1954
1955
1956
1957
1958
1959
1960
1961
1962
1963
1964
1965
1966
1967
1968
1969
1970
1971
1972
1973
1974
1975
1976
1977
1978
1979
1980
1981
1982
1983
1984
1985
1986
1987
1988
1989
1990
1991
1992
1993
1994
1995
1996
1997
1998
1999
2000
2001
2002
2003
2004
2005
2006
2007
2008
2009
2010
2011
2012
2013
2014
2015
2016
2017
2018
2019
2020
2021
2022
2023
2024
2025
2026
2027
2028
2029
2030
2031
2032
2033
2034
2035
2036
2037
2038
2039
2040
2041
2042
2043
2044
2045
2046
2047
2048
2049
2050
2051
2052
2053
2054
2055
2056
2057
2058
2059
2060
2061
2062
2063
2064
2065
2066
2067
2068
2069
2070
2071
2072
2073
2074
2075
2076
2077
2078
2079
2080
2081
2082
2083
2084
2085
2086
2087
2088
2089
2090
2091
2092
2093
2094
2095
2096
2097
2098
2099
2100
2101
2102
2103
2104
2105
2106
2107
2108
2109
2110
2111
2112
2113
2114
2115
2116
2117
2118
2119
2120
2121
2122
2123
2124
2125
2126
2127
2128
2129
2130
2131
2132
2133
2134
2135
2136
2137
2138
2139
2140
2141
2142
2143
2144
2145
2146
2147
2148
2149
2150
2151
2152
2153
2154
2155
2156
2157
2158
2159
2160
2161
2162
2163
2164
2165
2166
2167
2168
2169
2170
2171
2172
2173
2174
2175
2176
2177
2178
2179
2180
2181
2182
2183
2184
2185
2186
2187
2188
2189
2190
2191
2192
2193
2194
2195
2196
2197
2198
2199
2200
2201
2202
2203
2204
2205
2206
2207
2208
2209
2210
2211
221